

INDEX: VLE-TF05W

TECHNICAL CARD



LED Dimmable Desk Lamp













INDEX: VLE-TF05W











Ra ≥ 80

25 000

Free







WARRANTY 2 YEARS

ochiciai paramicicio	General	parameters
----------------------	---------	------------

Light source or containing product	Containing product
Control gear replaceable	yes
Light source replaceable	no

Type of light source

Dimmable	5-step
Energy efficiency class of the contained light source	F

Electrical parameters

Rated voltage, frequency	AC 100-240 V, 50/60 Hz
Rated current	45 mA
Input interface	AC adapter
Electric shock protection class	II

Photometric parameters

Useful luminous flux of the contained light source (Φ use)	Lm
------------------------------------------------------------------	----

Correlated color temperature	5500K (cold white), 4000K (neutral white), 3000K (warm white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
On/Off cycles	25000
Lifetime (L70B50)	30000 h
Useful luminous flux of the light source reference	in a sphere (360°)

Additional information

Place of installation	Desk
Place of application	indoor
Housing colour	White
Ultraviolet radiation	no
Operating temperature range	-10° +40°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Plastic

Dimensions

EAN	5904405541234
Height	329 mm
Depth	150 mm
In the package	1 pc.
Outer box	16 pcs.
Width	150 mm



INDEX: VLE-TF05W

Signs marking goods

Packaging marking

Recycling of waste, CE, Utilization










INDEX: VLE-TF05W











INDEX: VLE-TF05W

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product must be used indoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



Waste recycling after the end of the product's service



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with



Rated beam angle



Ra > 80 - color rendering index



Rated On/off cycles



Nominal lifetime (hours)



The product does not emit ultraviolet light



The product has 5-level brightness adjustment



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture

Date: 2.08.2025