

## TECHNICAL CARD



LED Dimmable Desk Lamp

## INDEX: VL-TF15W



## WARRANTY 2 YEARS

### General parameters

Light source or containing product	Containing product
Control gear replaceable	yes
Light source replaceable	no

### Type of light source

Dimmable	non-step dimming
Directional (DLS) or non-directional (NDLS) light source	NDLS
Color-tunable light source	no
Mains (MLS) or non-mains (NMLS) light source	NMLS
Technology	LED
Energy efficiency class of the contained light source	F

### Electrical parameters

On-mode power (Pon)	15 W
Rated voltage, frequency	AC 100-240 V, 50/60 Hz
Rated current	150 mA

Input interface	AC adapter
Electric shock protection class	II
Displacement factor (cos φ1)	-
Survival factor	1

### Photometric parameters

Useful luminous flux of the contained light source (Φuse)	1450 Lm
Correlated color temperature	4100K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra ≤ 98
On/Off cycles	100000
Lifetime (L70B50)	40000 h
Useful luminous flux of the light source reference	in a sphere (360°)
Chromaticity coordinates (x)	0.38
Chromaticity coordinates (y)	0.38
R9 colour rendering index value	>0
The lumen maintenance factor	≥96%
Flicker metric (Pst LM)	-
Stroboscopic effect metric (SVM)	-
Colour consistency in MacAdam ellipses (SDCM)	<6 (4100K)

### Additional information

Place of installation	Desk
Place of application	indoor
Housing colour	White

**VIDEX®**
**VIDEX TF15W 20W 4100K White**
**INDEX: VL-TF15W**

<b>Ultraviolet radiation</b>	no
<b>Operating temperature range</b>	-10° +40°C
<b>Mercury content</b>	Does not contain
<b>Ingress protection</b>	IP20
<b>Housing material</b>	Aluminum, PC, ABS, Acrylic

### Dimensions

<b>EAN</b>	4820246482318
<b>Height</b>	601 mm
<b>Depth</b>	162 mm
<b>In the package</b>	1 pc.
<b>Outer box</b>	4 pcs.
<b>Width</b>	162 mm
<b>Unit nett weight</b>	1500g

### Signs marking goods

<b>Packaging marking</b>	CE, Utilization
--------------------------	-----------------



**VIDEX®**

VIDEX TF15W 20W 4100K White

**INDEX: VL-TF15W**


# VIDEX®


VIDEX TF15W 20W 4100K White

INDEX: VL-TF15W



Built-in touch sensor for quick gesture control and automatic brightness detection



**INDEX: VL-TF15W**


We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



The product must be used indoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



120°

— Rated beam angle



— Rated On/off cycles



— Nominal lifetime (hours)



Free

— The product does not emit ultraviolet light



Dimmable

— The product has smooth brightness adjustment



— Operating temperatures range



— Colour consistency in MacAdam ellipses (SDCM)



Free

— The product does not contain mercury



— Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture