

## TECHNICAL CARD



LED Dimmable Desk Lamp



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.



120°



Free



Dimmable



CCT 4100K



Free



IP20

## WARRANTY 2 YEARS

### General parameters

Control gear replaceable	yes
Light source replaceable	no
Light source or containing product	Containing product

### Type of light source

Energy class of the light source	F
Dimmable	non-step dimming
Directional or non-directional light source	NDLS
Mains or non-mains light source	NMLS
Colour-tuneable light source (CTLS)	no
Technology	LED

### Electrical parameters

On-mode power (Pon)	15 W
Rated voltage, frequency	AC 100-240 V, 50/60 Hz
Rated current	150 mA
Input interface	AC adapter

## VIDEX TF15W 20W 4100K White

### INDEX: VL-TF15W

Electric shock protection class	II
Displacement factor (cos φ1)	-
Survival factor	1

### Photometric parameters

Useful luminous flux of the light source (Φuse)	1450 Lm
Correlated color temperature	4100K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra ≤ 98
Lifetime	40000 h
On/Off cycles	100000
Useful luminous flux of the light source reference	in a sphere (360°)
Chromaticity coordinates (x)	0.38
Chromaticity coordinates (y)	0.38
R9 colour rendering index value	>0
The lumen maintenance factor	≥96%
Colour consistency in MacAdam ellipses (SDCM)	<6 (4100K)
Flicker metric (Pst LM)	-
Stroboscopic effect metric (SVM)	-

### Additional information

Place of installation	Desk
Place of application	indoor
Housing colour	White
Ultraviolet radiation	no

# VIDEX®

## VIDEX TF15W 20W 4100K White

### INDEX: VL-TF15W

<b>Operating temperature range</b>	-10° +40°C
<b>Mercury content</b>	Does not contain
<b>Ingress protection</b>	IP20
<b>Housing material</b>	Aluminum, PC, ABS, Acrylic
<b>Dimensions</b>	
<b>EAN</b>	4820246482318
<b>Height</b>	601 mm
<b>Width</b>	162 mm
<b>Depth</b>	162 mm
<b>Outer box</b>	4 pcs.
<b>Unit nett weight</b>	1500g
<b>In the package</b>	1 pc.

### Signs marking goods

<b>Packaging marking</b>	CE, Utilization
--------------------------	-----------------



**VIDEX®**

VIDEX TF15W 20W 4100K White

**INDEX: VL-TF15W**


# VIDEX®

VIDEX TF15W 20W 4100K White

INDEX: VL-TF15W



Built-in touch sensor for quick gesture control and automatic brightness detection



**INDEX: VL-TF15W**

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.

