

INDEX: VL-TF15W

TECHNICAL CARD



LED Dimmable Desk Lamp











INDEX: VL-TF15W











Dimmable









۸			C)
)/	^	V	
~	۲.			١
•	U	5	J	
		_		

°r	Ω=	
	∭≡ □	
1	•	
10°	+40°C	

CCT 4100K

IP20

Input interface	AC adapter
Electric shock protection class	II
Displacement factor (cos φ1)	-
Survival factor	1

WARRANTY 2 YEARS

General parameters

Light source or containing product	Containing product
Control gear replaceable	yes
Light source replaceable	no

Type of light source

Dimmable	non-step dimming
Directional (DLS) or non-directional (NDLS) light source	NDLS
Color-tunable light source	no
Mains (MLS) or non-mains (NMLS) light source	NMLS
Technology	LED
Energy efficiency class of the contained light source	F

Electrical parameters

On-mode power (Pon)	15 W
Rated voltage, frequency	AC 100-240 V, 50/60 Hz
Rated current	150 mA

Photometric parameters

Useful luminous flux of the contained light source (Φ use)	1450 Lm
Correlated color temperature	4100K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra ≤ 98
On/Off cycles	100000
Lifetime (L70B50)	40000 h
Useful luminous flux of the light source reference	in a sphere (360°)
Chromaticity coordinates (x)	0.38
Chromaticity coordinates (y)	0.38
R9 colour rendering index value	>0
The lumen maintenance factor	≥96%
Flicker metric (Pst LM)	-
Stroboscopic effect metric (SVM)	-
Colour consistency in MacAdam ellipses (SDCM)	<6 (4100K)

Additional information

Place of installation	Desk
Place of application	indoor
Housing colour	White



INDEX: VL-TF15W

Ultraviolet radiation	no	
Operating temperature range	-10° +40°C	
Mercury content	Does not contain	
Ingress protection	IP20	
Housing material	Aluminum, PC, ABS, Acrylic	

Dimensions

EAN	4820246482318
In the package	1 pc.
Height	601 mm
Outer box	4 pcs.
Width	162 mm
Depth	162 mm
Unit nett weight	1500g

Signs marking goods

Packaging marking	CE, Utilization
-------------------	-----------------







INDEX: VL-TF15W





INDEX: VL-TF15W




Built-in touch sensor for quick gesture control and automatic brightness detection









We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

VIDEX TF15W 20W 4100K White

INDEX: VL-TF15W



The product must be used indoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Rated beam angle



Rated On/off cycles



Nominal lifetime (hours)



The product does not emit ultraviolet light



The product has smooth brightness adjustment



Operating temperatures range



Colour consistency in MacAdam ellipses (SDCM)



The product does not contain mercury



Free

Class of protection against dust and moisture.
Protection against solid objects larger than 12 mm; no protection against moisture

Date: 18.11.2025