

INDEX: VLE-DLBR-124B

TECHNICAL CARD



LED Recessed Downlight













VIDEX-DOWNLIGHT-LED-DLBR-124-BLACK-12W-NW

INDEX: VLE-DLBR-124B



120°









Free







Ra ≥ 80











IP20

WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Light source or containing product	Containing product
Control gear replaceable	-
Light source replaceable	by the producer

Type of light source

Dimmable	no
Directional (DLS) or non-directional (NDLS) light source	NDLS
Connected light source (cls)	no
Color-tunable light source	no
Mains (MLS) or non-mains (NMLS) light source	MLS

High luminance light source	No
Anti-glare shield	No
Technology	LED
Energy efficiency class of the contained light source	E

Electrical parameters

On-mode power (Pon)	12 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	130 mA
Input interface	Free wire ends
Electric shock protection class	II
Displacement factor (cos φ1)	0.7
Survival factor	0.9
Energy consumption in on-mode of the light source (kWh/1000h)	12

Photometric parameters

Useful luminous flux of the contained light source (Фuse)	1350 Lm
Correlated color temperature	4000K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	30000 h
Useful luminous flux of the light source reference	in a sphere (360°)
Chromaticity coordinates (x)	0.38



VIDEX-DOWNLIGHT-LED-DLBR-124-BLACK-12W-NW

INDEX: VLE-DLBR-124B

Chromaticity coordinates (y)	0.38
R9 colour rendering index value	>0
The lumen maintenance factor	≥96%
Flicker metric (Pst LM)	≤1
Stroboscopic effect metric (SVM)	≤0.4
Colour consistency in MacAdam ellipses (SDCM)	<6 (4000K)
CRI Min	Ra 80
CRI Max	Ra 89

Width	175 mm
Depth	27 mm
Unit nett weight	126g

Signs marking goods

De also sinos su audinos	Recycling of
Packaging marking	waste, CE,
	Utilization

Additional information

Place of installation	Ceiling, Recessed
Place of application	indoor
Housing colour	Black
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Suitable for installation in normally flammable surfaces	yes
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Plastic





Dimensions


EAN	5904405542637
In the package	1 pc.
Outer box	20 pcs.
Height	175 mm



VIDEX-DOWNLIGHT-LED-DLBR-124-BLACK-12W-NW

INDEX: VLE-DLBR-124B







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,

30-732 Krakow, Poland. The product must be used indoors

Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation The product can be installed and used in/on normally flammable

Waste recycling after the end of the product's service life

The product meets the requirements of EU directives

Q It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste $\,$

120°
Ra ≥ 80
ONOFF
20 000
30 000 h Rated beam angle Ra > 80 - color rendering index

Rated On/off cycles

Nominal lifetime (hours)

The product does not emit ultraviolet light

The product is incompatible with light regulators Operating temperatures range

No Flicker The flickering of the light does not exceed the permissible level The product has minimal flickering, which should not cause

Colour consistency in MacAdam ellipses (SDCM) **⊮**g

The product does not contain mercury

Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture

Date: 26.11.2025