

TECHNICAL CARD



LED Downlight Fixture



VIDEX®



120°



Ra ≥ 80



30 000 h

ON/OFF
20 000

Free



-20° +40°C



Not Dimmable



Free



IP20

WARRANTY 2 YEARS

NEUTRAL WHITE



4000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

General parameters

Control gear replaceable	-
Light source replaceable	by the producer

Type of light source

Energy class of the light source	F
Dimmable	no

Electrical parameters

On-mode power (Pon)	6 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	45 mA
Input interface	Free wire ends
Electric shock protection class	II

VIDEX-DOWNLIGHT-LED-DLBS-064-6W-NW

INDEX: VLE-DLBS-064

Photometric parameters

Useful luminous flux of the contained light source (Φuse)	620 Lm
Correlated color temperature	4000K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
Lifetime	30000 h
On/Off cycles	20000
Useful luminous flux of the light source reference	in a sphere (360°)

Additional information


Place of installation	Ceiling, Recessed
Place of application	indoor
Housing colour	White
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Plastic

Dimensions

EAN	5904405540893
Height	120 mm
Width	120 mm


VIDEX®

VIDEX-DOWNLIGHT-LED-DLBS-064-6W-NW

INDEX: VLE-DLBS-064**Depth** 27 mm**Outer box** 40 pcs.

INDEX: VLE-DLBS-064

30-732 Krakow, Poland.



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,



The product must be used indoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



120°

Rated beam angle



Ra > 80

Ra > 80 - color rendering index



30 000 h

Nominal lifetime (hours)



20 000

Rated On/off cycles



Free

The product does not emit ultraviolet light



-20° +40°C

Operating temperatures range



Not Dimmable

The product is incompatible with light regulators



Free

The product does not contain mercury



IP20

Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture