

**INDEX: VLE-DLBS-184** 

## **TECHNICAL CARD**



LED Downlight Fixture







#### VIDEX-DOWNLIGHT-LED-DLBS-184-18W-NW

#### **INDEX: VLE-DLBS-184**











Ra ≥ 80

20 000

Free

Not Dimmable







# WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutra

#### **General parameters**

Light source or containing product	Containing product
Control gear replaceable	-
Light source replaceable	by the producer

#### Type of light source

Dimmable	no
Energy efficiency class of the contained light source	E

#### **Electrical parameters**

On-mode power (Pon)	18 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	130 mA

Input interface	Free wire ends
Electric shock protection class	II

#### **Photometric parameters**

Useful luminous flux of the contained light source (Фuse)	2200 Lm
Correlated color temperature	4000K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	30000 h
Useful luminous flux of the light source reference	in a sphere (360°)

#### **Additional information**

Place of installation	Ceiling, Recessed
Place of application	indoor
Housing colour	White
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Plastic

#### **Dimensions**

,
,



### VIDEX-DOWNLIGHT-LED-DLBS-184-18W-NW

#### **INDEX: VLE-DLBS-184**

Height	224 mm
Outer box	20 pcs.
Width	224 mm
Depth	28 mm












#### VIDEX-DOWNLIGHT-LED-DLBS-184-18W-NW

**INDEX: VLE-DLBS-184** 





We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product must be used indoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



Rated beam angle



Ra > 80 - color rendering index



Rated On/off cycles





Nominal lifetime (hours)



The product does not emit ultraviolet light



The product is incompatible with light regulators



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture

Date: 18.11.2025