



INDEX: VL-AR09061B

TECHNICAL CARD



Led Fixture Architectural















VIDEX VL-AR09061B

INDEX: VL-AR09061B









| Ingress protection | IP54 |
|--------------------|----------|
| Housing material | Aluminum |

WARRANTY 2 YEARS

General parameters

| end user |
|----------|
| |

Type of light source

| Technology | LED |
|------------|-----|

Electrical parameters

| Rated voltage, frequency | AC 220-240 V, 50/60 Hz |
|---------------------------------|---------------------------|
| Input interface | Terminal block |
| Electric shock protection class | |

Additional information

| Place of installation | Floor |
|--|-----------------------|
| Place of application | indoor, outdoor |
| Impact protection | IK07 |
| Housing colour | Black |
| Diffuser material | Polycarbonate (PC) |
| Operating temperature range | -25° +50°C |
| Suitable for installation in normally flammable surfaces | yes |
| Mercury content | Does not contain |

Dimensions

| EAN | 4820246485975 |
|------------------|---------------|
| In the package | 1 pc. |
| Height | 600 mm |
| Outer box | 10 pcs. |
| Width | 60 mm |
| Depth | 80 mm |
| Unit nett weight | 1kg |

Signs marking goods

| E, Utilization |
|----------------|
| |







VIDEX VL-AR09061B

INDEX: VL-AR09061B














We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,

VIDEX VL-AR09061B

INDEX: VL-AR09061B

30-732 Krakow, Poland.



The product must be used indoors



The product must be used outdoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



The product can be installed and used in/on normally flammable surfaces



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



The product withstands a medium impact (e.g., from a blunt object)



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. The product is protected against the ingress of water and dust particles into the housing

Date: 18.11.2025