

VIDEX VL-AR092B

**INDEX: VL-AR092B** 

# **TECHNICAL CARD**





Led Fixture Architectural





















## VIDEX VL-AR092B

### **INDEX: VL-AR092B**

Ingress protection	IP54
Housing material	Aluminum

### **WARRANTY 2 YEARS**

## **General parameters**

Light source replaceable	end user
Type of light source	
Technology	LED

## **Electrical parameters**

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Terminal block
Electric shock protection class	I

## **Additional information**

Place of installation	Wall
Place of application	indoor, outdoor
Impact protection	IK07
Housing colour	Black
Diffuser material	Polycarbonate (PC)
Operating temperature range	-25° +50°C
Suitable for installation in normally flammable surfaces	yes
Mercury content	Does not contain

### **Dimensions**

EAN	4820246485968
In the package	1 pc.
Height	305 mm
Outer box	20 pcs.
Width	60 mm
Depth	80 mm
Unit nett weight	540g

## Signs marking goods

Packaging marking	CE, Utilization
i ackaging marking	CL, Othization





## VIDEX VL-AR092B

**INDEX: VL-AR092B** 











We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,

### VIDEX VL-AR092B

#### **INDEX: VL-AR092B**

#### 30-732 Krakow, Poland.



The product must be used indoors



The product must be used outdoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



The product can be installed and used in/on normally flammable surfaces



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



The product withstands a medium impact (e.g., from a blunt object)



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. The product is protected against the ingress of water and dust particles into the housing

Date: 18.11.2025