


VIDEX®

VIDEX VL-AR092B

INDEX: VL-AR092B

TECHNICAL CARD



Led Fixture Architectural



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



IK07



-25° +50°C



Free



IP54

WARRANTY 2 YEARS

General parameters

Light source replaceable end user

Type of light source

Technology LED

Electrical parameters

Rated voltage, frequency AC 220-240 V, 50/60 Hz

Input interface Terminal block

Electric shock protection class I

Additional information

Place of installation Wall

Place of application indoor, outdoor

Impact protection IK07

Housing colour Black

Diffuser material Polycarbonate (PC)

Operating temperature range -25° +50°C

Suitable for installation in normally flammable surfaces yes

Mercury content Does not contain

VIDEX VL-AR092B

INDEX: VL-AR092B

Ingress protection IP54

Housing material Aluminum

Dimensions

EAN 4820246485968

Height 305 mm

Width 60 mm

Depth 80 mm


Outer box 20 pcs.

Unit nett weight 540g

In the package 1 pc.

Signs marking goods

Packaging marking CE, Utilization



VIDEX®

VIDEX VL-AR092B

INDEX: VL-AR092B

INDEX: VL-AR092B

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.

