

# VIDEX®

VIDEX-FLOOD-LED-DAVIS-200W-NW

INDEX: VL-F2-2005G

## TECHNICAL CARD



LED Floodlight




Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

# VIDEX®

## VIDEX-FLOOD-LED-DAVIS-200W-NW

### INDEX: VL-F2-2005G



## WARRANTY 3 YEARS

NEUTRAL WHITE

5000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

## General parameters

Control gear replaceable	no
Light source replaceable	no
Light source or containing product	Light source

## Type of light source

Energy class of the light source	D
Dimmable	no
Directional or non-directional light source	DLS
Mains or non-mains light source	MLS
Connected light source (cls)	no
Colour-tuneable light source (CTLS)	no
High luminance light source	No

Anti-glare shield	No
Technology	LED

## Electrical parameters

On-mode power (Pon)	200 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	960 mA
Input interface	Free wire ends
Electric shock protection class	I
Energy consumption in on-mode of the light source (kWh/1000h)	200
Displacement factor (cos φ1)	0.9
Survival factor	0.9

## Photometric parameters

Useful luminous flux of the light source (Φuse)	24000 Lm
Correlated color temperature	5000K (neutral white)
Peak luminous intensity	13000 cd
Beam angle	90°
Color rendering index (CRI)	Ra > 80
Lifetime	30000 h
On/Off cycles	20000
Useful luminous flux of the light source reference	in a wide cone (120°)
Chromaticity coordinates (x)	0.34
Chromaticity coordinates (y)	0.359

# VIDEX®

## VIDEX-FLOOD-LED-DAVIS-200W-NW

### INDEX: VL-F2-2005G

<b>R9 colour rendering index value</b>	>0
<b>The lumen maintenance factor</b>	≥96%
<b>Colour consistency in MacAdam ellipses (SDCM)</b>	<6 (6500K)
<b>Flicker metric (Pst LM)</b>	≤1
<b>Stroboscopic effect metric (SVM)</b>	outdoor use

<b>Depth</b>	33 mm
<b>Outer box</b>	5 pcs.
<b>In the package</b>	1 pc.


### Additional information

<b>Place of installation</b>	Ceiling, Flat surface, Wall
<b>Vertical adjustment range</b>	180°
<b>Place of application</b>	outdoor
<b>Impact protection</b>	IK07
<b>Housing colour</b>	Gray
<b>Minimum distance from the illuminated object</b>	0.5 m
<b>Diffuser material</b>	Polycarbonate (PC)
<b>Motion sensor</b>	no
<b>Operating temperature range</b>	-20° +50°C
<b>Suitable for installation in normally flammable surfaces</b>	yes
<b>Mercury content</b>	Does not contain
<b>Ingress protection</b>	IP65
<b>Housing material</b>	Aluminum

### Dimensions

<b>EAN</b>	5904405542156
<b>Height</b>	338 mm
<b>Width</b>	305 mm



**INDEX: VL-F2-2005G**

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.