

INDEX: VLE-DLFR-154

TECHNICAL CARD



LED Frameless Downlight Fixture







INDEX: VLE-DLFR-154





Ra ≥ 80







0 30 000 h

Free









Input interface Free wire ends Electric shock protection class II

WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutra

General parameters

Light source or containing product	Containing product
Control gear replaceable	by the producer
Light source replaceable	by the producer

Type of light source

Dimmable	no
Energy efficiency class of the contained light source	Е

Electrical parameters

Rated voltage, frequency	AC 85-265 V, 50/60 Hz
Rated current	130 mA

Photometric parameters

Useful luminous flux of the contained light source (Φ use)	1950 Lm
Correlated color temperature	4000K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	30000 h
Useful luminous flux of the light source reference	in a sphere (360°)

Additional information

Place of installation	Ceiling, Recessed
Place of application	indoor
Housing colour	White
Diffuser material	Plastic
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP54 / IP20
Housing material	Iron alloy

Dimensions




INDEX: VLE-DLFR-154

EAN	5904405540794
Outer box	20 pcs.
Height	120 mm
Width	120 mm
Depth	20 mm









We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



4/4

INDEX: VLE-DLFR-154



The product must be used indoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



Rated beam angle



Ra > 80 – color rendering index



Rated On/off cycles



Nominal lifetime (hours)



The product does not emit ultraviolet light



The product is incompatible with light regulators





Operating temperatures range



The product does not contain mercury



IP54 - external part, IP20 - mounting part

Date: 18.11.2025