

## TECHNICAL CARD



LED Frameless Downlight Fixture



# VIDEX®



120°



Ra ≥ 80



ON/OFF

20 000



30 000 h



Free



Not Dimmable



-20° +40°C



Free



IP20

↓ IP54

## WARRANTY 2 YEARS

### NEUTRAL WHITE



### 4000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevrtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

## General parameters

<b>Light source or containing product</b>	Containing product
<b>Control gear replaceable</b>	by the producer
<b>Light source replaceable</b>	by the producer

## Type of light source

**Energy efficiency class of the contained light source** E

**Dimmable** no

## Electrical parameters

**Rated voltage, frequency** AC 85-265 V, 50/60 Hz

**Rated current** 130 mA

## VIDEX-DOWNLIGHT-LED-DLFS-15W-NW

### INDEX: VLE-DLFS-154

<b>Input interface</b>	Free wire ends
<b>Electric shock protection class</b>	II

## Photometric parameters

<b>Useful luminous flux of the contained light source (Φuse)</b>	2100 Lm
<b>Correlated color temperature</b>	4000K (neutral white)
<b>Beam angle</b>	120°
<b>Color rendering index (CRI)</b>	Ra > 80
<b>On/Off cycles</b>	20000
<b>Lifetime (L70B50)</b>	30000 h
<b>Useful luminous flux of the light source reference</b>	in a sphere (360°)

## Additional information

<b>Place of installation</b>	Ceiling, Recessed
<b>Place of application</b>	indoor
<b>Housing colour</b>	White
<b>Diffuser material</b>	Plastic
<b>Ultraviolet radiation</b>	no
<b>Operating temperature range</b>	-20° +40°C
<b>Mercury content</b>	Does not contain
<b>Ingress protection</b>	IP54 / IP20
<b>Housing material</b>	Iron alloy


## Dimensions

# VIDEX®

## VIDEX-DOWNLIGHT-LED-DLFS-15W-NW

### INDEX: VLE-DLFS-154

<b>EAN</b>	5904405540824
<b>Height</b>	120 mm
<b>Outer box</b>	20 pcs.
<b>Width</b>	120 mm
<b>Depth</b>	20 mm



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.

## INDEX: VLE-DLFS-154



The product must be used indoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



— Rated beam angle



— Ra > 80 - color rendering index



— Rated On/off cycles



— Nominal lifetime (hours)



— The product does not emit ultraviolet light



— The product is incompatible with light regulators



— Operating temperatures range



— The product does not contain mercury



— IP54 - external part, IP20 - mounting part