



INDEX: VLE-DLFS-244

TECHNICAL CARD



LED Frameless Downlight Fixture







VIDEX-DOWNLIGHT-LED-DLFS-24W-NW

INDEX: VLE-DLFS-244











120° Ra

Ra ≥ 80

20 000 30

30 000 h

Free



Not Dimmable







WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutra

General parameters

Light source or containing product	Containing product
Control gear replaceable	by the producer
Light source replaceable	by the producer

Type of light source

Dimmable	no

Electrical parameters

Rated voltage, frequency	AC 85-265 V, 50/60 Hz
Rated current	210 mA

Input interface	Free wire ends
Electric shock protection class	II

Photometric parameters

Useful luminous flux of the contained light source (Фuse)	3200 Lm
Correlated color temperature	4000K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	30000 h
Useful luminous flux of the light source reference	in a sphere (360°)

Additional information

Place of installation	Ceiling, Recessed
Place of application	indoor
Housing colour	White
Diffuser material	Plastic
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP54 / IP20
Housing material	Iron alloy

Dimensions



VIDEX-DOWNLIGHT-LED-DLFS-24W-NW

INDEX: VLE-DLFS-244


EAN	5904405540831
Height	175 mm
Outer box	20 pcs.
Width	175 mm
Depth	20 mm











We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,

VIDEX-DOWNLIGHT-LED-DLFS-24W-NW

INDEX: VLE-DLFS-244

30-732 Krakow, Poland.

The product must be used indoors

Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation

Rated beam angle

Ra > 80 - color rendering index

ON/0FF 20 000

Rated On/off cycles

(7) 30 000 h

Nominal lifetime (hours)

The product does not emit ultraviolet light



The product is incompatible with light regulators



Operating temperatures range

l/g

The product does not contain mercury

IP54 - external part, IP20 - mounting part

Date: 18.11.2025