

INDEX: VLF-A056H

TECHNICAL CARD



LED Headlamp



VIDEX VLF-A056H 200Lm 5000K

INDEX: VLF-A056H

2m SHOCK RESISTANT









WARRANTY 3 YEARS

General parameters

Operation mode	HIGH, MIDDLE, LOW, RED HIGH, RED LOW, RED FLASH
Light source replaceable	no
Battery Warranty	1 year

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	10 W
Input interface	USB-C in battery

Photometric parameters

Useful luminous flux of the contained light source (Фиѕе)	200 Lm
Correlated color temperature	5000K (neutral white), Red
Peak luminous intensity	1100 cd

Additional information

Housing colour	Black
Fall protection	2 m
Operating temperature range	-20° +40°C
Battery voltage	1.5 V
Battery capacity	2200 mAh
Battery type	Li-ion
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP68
Housing material	Aviation anodized aluminum

Dimensions

EAN	4820246488112
In the package	1 pc.
Outer box	20 pcs.
Height	74 mm
Width	20.5 mm
Depth	21 mm
Unit nett weight	75g

Signs marking goods

Packaging marking	CE, Utilization





INDEX: VLF-A056H











VIDEX VLF-A056H 200Lm 5000K

INDEX: VLF-A056H













INDEX: VLF-A056H









VIDEX VLF-A056H 200Lm 5000K

INDEX: VLF-A056H



We reserve the right to make technical changes. The data contained in this material is

not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



 The protection is effective in case of a fall from a height of up to 2 meters



- The product is incompatible with light regulators



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture.
The product has full protection against dust and prolonged immersion in water at a depth of more than 1 meter

Date: 18.11.2025