

VIDEX[®]

VIDEX VLF-H015 330Lm 5000K

INDEX: VLF-H015

TECHNICAL CARD



LED Headlamp



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



WARRANTY 2 YEARS

NEUTRAL WHITE



5000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevturalno bela / Neutrnalno bijela / Neutralweiß / Alb neutru / Neutrnalus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

General parameters

Light source replaceable no

Type of light source

Dimmable no

Technology LED

Electrical parameters

On-mode power (Pon) 5 W

Input interface USB-C

Photometric parameters

Useful luminous flux of the light source (Φ_{use}) 330 Lm

Correlated color temperature 5000K (neutral white)

Peak luminous intensity 1800 cd

VIDEX VLF-H015 330Lm 5000K

INDEX: VLF-H015

Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP67
Housing material	PC

Dimensions

EAN	4820246480987
Height	32 mm
Width	65 mm
Depth	35 mm
Outer box	20 pcs.
Unit nett weight	73g
In the package	1 pc.

Signs marking goods

Packaging marking CE, Utilization

VIDEX®

VIDEX VLF-H015 330lm 5000K

INDEX: VLF-H015



VIDEX®

VIDEX VLF-H015 330Lm 5000K

INDEX: VLF-H015



VIDEX®
MODEL | HO15

RECHARGEABLE LED HEADLAMP
WITH SENSOR

330
MAX LUMENS

- LIGHTWEIGHT
- TYPE-C
- IP67
- SHOCKPROOF
- RED LIGHT

INDEX: VLF-H015



VIDEX®

VIDEX VLF-H015 330Lm 5000K

INDEX: VLF-H015



VIDEX®

VIDEX VLF-H015 330Lm 5000K

INDEX: VLF-H015



VIDEX®

VIDEX VLF-H015 330Lm 5000K

INDEX: VLF-H015

VIDEX® LIGHTING MODES
MODEL | HO15



LIGHTING MODES	HIGH	LOW	STROBE	RED ON	RED FLASH
OUTPUT	330 Lm	105 Lm	330 Lm	3 Lm	3 Lm
RUNTIME	3h	3h 30min	3h	13h 30min	27h
DISTANCE	85m	53m	85	/	/
INTENSITY	1800cd	696cd	1800cd	/	/

VIDEX® PROGRAM ROOT
MODEL | HO15



* Sensor remembers current lighting mode and applies it until the sensor mode will be deactivated.

VIDEX® KIT CONTENT
MODEL | HO15



USER'S MANUAL HEADLAMP HEADBAND CHARGING CABLE

SIZES 65x35x32mm
WEIGHT: 73g (including headband)

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.