

TECHNICAL CARD



LED Headlamp

VIDEX®



WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrálno bijela / Neutralweiß / Alb neutru / Neutrus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Operation mode	HIGH, LOW, STROBE, RED ON, RED FLASH
Light source replaceable	no

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	5 W
Input interface	USB-C

Photometric parameters

Useful luminous flux of the contained light source (Φuse)	330 Lm
---	--------

VIDEX VLF-H015 330Lm 5000K

INDEX: VLF-H015

Correlated color temperature	5000K (neutral white)
Peak luminous intensity	1800 cd

Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery type	Li-ion
Battery voltage	3.7 V
Battery capacity	850 mAh
Battery indicator	4 level
Battery replaceable	no
Mercury content	Does not contain
Ingress protection	IP67
Housing material	PC

Dimensions

EAN	4820246480987
Height	32 mm
Depth	35 mm
In the package	1 pc.
Outer box	20 pcs.
Width	65 mm
Unit nett weight	73g

Signs marking goods

VIDEX®

VIDEX VLF-H015 330Lm 5000K

INDEX: VLF-H015

Packaging marking

CE, Utilization



VIDEX[®]

VIDEX VLF-H015 330Lm 5000K

INDEX: VLF-H015**VIDEX[®]**
MODEL | **H015**RECHARGEABLE LED HEADLAMP
WITH SENSOR**330**
MAX LUMENS
LIGHTWEIGHT
USB-C
IP67
SHOCKPROOF


1m


RED LIGHT

VIDEX®

VIDEX VLF-H015 330Lm 5000K

INDEX: VLF-H015



VIDEX®

VIDEX VLF-H015 330Lm 5000K

INDEX: VLF-H015

VIDEX®
MODEL | H015



FOUR-LEVEL INDICATOR

Battery charge indicator gives more precise information about current charge status.

- ● ● ● - ≤ 25% charge
- ● ● ● - ≤ 50% charge
- ● ● ● - ≤ 75% charge
- ● ● ● - ≤ 100% charge

VIDEX®
MODEL | H015

POWER BUTTON



Power button turns ON/OFF the light and changes the modes.

VIDEX®
MODEL | H015

SWIFT TOUCHLESS CONTROL

SENSOR BUTTON




With built-in motion sensor you can turn on/off the light by a hand wave.

VIDEX®
MODEL | H015

RED LIGHT PRESERVES NIGHT VISION



Unlike white light, the red light does not affect your night vision, so it is suitable for use while being in groups.
Red flash. When it is needed to give a signal, the red light is visible both at night and during the day. Therefore, it perfectly copes with this task.



The red light does not affect your night vision



The red flash is visible both at night and during the day

VIDEX®

VIDEX VLF-H015 330Lm 5000K

INDEX: VLF-H015



VIDEX®

VIDEX VLF-H015 330Lm 5000K

INDEX: VLF-H015

VIDEX® LIGHTING MODES
MODEL | HO15



LIGHTING MODES	HIGH	LOW	FLASH	RED ON	RED FLASH
OUTPUT	330 Lm	105 Lm	330 Lm	3 Lm	3 Lm
RUNTIME	3h	3h 30min	3h	13h 30min	27h
DISTANCE	85m	53m	85m	/	/
INTENSITY	1800cd	696cd	1800cd	/	/


VIDEX® PROGRAM ROOT
MODEL | HO15



Start position	Action A	Result	Action B	Result
OFF	Press	ON SENSOR	Hand wave	OFF/ON
* HIGH / LOW / FLASH / RED ON / RED FLASH	Press	SENSOR *	Hand wave	OFF/ON *
OFF	Press and hold for 0.5 sec	Battery status		
OFF	Press and hold for 3 sec	Lock	Press and hold for 3 sec	Unlock
OFF	Press	> ON HIGH > LOW > FLASH > RED ON > RED FLASH > OFF >	Press and hold for 0.5 sec	OFF

* Sensor remembers current lighting mode and applies it until the sensor mode will be deactivated.

VIDEX® KIT CONTENT
MODEL | HO15



USER'S MANUAL HEADLAMP HEADBAND CHARGING CABLE USB-C

SIZES 65x35x32mm
WEIGHT: 73g (including headband)

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



1m
SHOCK
RESISTANT

— The protection is effective in case of a fall from a height of up to 1 meter



Not Dimmable

— The product is incompatible with light regulators



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP67

— Class of protection against dust and moisture. The product has full protection against dust and short-term immersion in water up to a depth of 1 meter

Date: 30.08.2025