

**INDEX: VLF-H045Z** 

# **TECHNICAL CARD**



LED Headlamp



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.



# VIDEX VLF-H045Z 270Lm 5000K

INDEX: VLF-H045Z

1m		°C	₩.
SHOCK RESISTANT	Not Dimmable	-20° +40°C	Free

**g** 

## WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

#### **General parameters**

Operation mode	HIGH, LOW, STROBE, RED ON, RED FLASH
Light source replaceable	no

#### Type of light source

Dimmable	no	
Technology	LED	
Electrical parameters		
On-mode power (Pon)	5 W	
Input interface	Micro USB	
Photometric parameters		
Useful luminous flux of the contained light source ( <b>Ф</b> use)	270 Lm	

Correlated color temperature	5000K (neutral white)
Peak luminous intensity	700 cd

## Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery type	Li-ion
Battery voltage	3.7 V
Battery capacity	1800 mAh
Battery indicator	5 level
Battery replaceable	no
Mercury content	Does not contain
Ingress protection	IP65
Housing material	PC

#### Dimensions

EAN	4820246481052
Height	46 mm
Depth	38 mm
In the package	1 pc.
Outer box	20 pcs.
Width	70 mm
Unit nett weight	122g

## Signs marking goods



# VIDEX VLF-H045Z 270Lm 5000K

INDEX: VLF-H045Z

## Packaging marking

CE, Utilization











# VIDEX VLF-H045Z 270Lm 5000K

INDEX: VLF-H045Z







INDEX: VLF-H045Z

not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

<b>CE T</b>	ne product meets the requirements of EU directives
🛛 🗶 ma	is forbidden to throw away waste equipment arked with the symbol of a crossed-out bin with her waste
IM SHOCK RESISTANT	The protection is effective in case of a fall from a height of up to 1 meter
Not Dimmable	The product is incompatible with light regulators
°C	Operating temperatures range
Free	The product does not contain mercury
₩ IP65	Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions



We reserve the right to make technical changes. The data contained in this material is