

TECHNICAL CARD



LED Headlamp

VIDEX®



WARRANTY 2 YEARS

General parameters

| | |
|--------------------------|--|
| Operation mode | TURBO, HIGH, MIDDLE, LOW, RED HIGH, RED MIDDLE, RED LOW, RED FLASH |
| Light source replaceable | no |

Type of light source

| | |
|------------|-----|
| Dimmable | yes |
| Technology | LED |

Electrical parameters

| | |
|-----------------|-------|
| Input interface | USB-C |
|-----------------|-------|

Photometric parameters

| | |
|--|----------------------------|
| Useful luminous flux of the contained light source (Φ _{use}) | 1000 Lm |
| Correlated color temperature | 5000K (neutral white), Red |
| Peak luminous intensity | 11660 cd |

Additional information

| | |
|----------------|-------|
| Housing colour | Black |
|----------------|-------|

VIDEX VLF-H047Z 1000Lm 5000K

INDEX: VLF-H047Z

| | |
|-----------------------------|------------------|
| Fall protection | 1 m |
| Operating temperature range | -20° +40°C |
| Battery voltage | 3.7 V |
| Battery type | Li-pol |
| Battery capacity | 2000 mAh |
| Battery indicator | 5 level |
| Battery replaceable | no |
| Mercury content | Does not contain |
| Ingress protection | IP65 |
| Housing material | Polyamide |

Dimensions

| | |
|------------------|---------------|
| EAN | 4820246489560 |
| In the package | 1 pc. |
| Height | 49 mm |
| Outer box | 20 pcs. |
| Width | 80 mm |
| Depth | 46 mm |
| Unit nett weight | 123g |

Signs marking goods

| | |
|-------------------|-----------------|
| Packaging marking | CE, Utilization |
|-------------------|-----------------|

VIDEX®

VIDEX VLF-H047Z 1000Lm 5000K

INDEX: VLF-H047Z

VIDEX[®]

VIDEX VLF-H047Z 1000Lm 5000K

INDEX: VLF-H047Z

VIDEX[®]

VIDEX VLF-H047Z 1000Lm 5000K

INDEX: VLF-H047Z

VIDEX[®]

VIDEX VLF-H047Z 1000Lm 5000K

INDEX: VLF-H047Z

VIDEX[®]

VIDEX VLF-H047Z 1000Lm 5000K

INDEX: VLF-H047Z

VIDEX®

VIDEX VLF-H047Z 1000Lm 5000K

INDEX: VLF-H047Z

not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



We reserve the right to make technical changes. The data contained in this material is



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 1 meter



Dimmable

— The product supports brightness adjustment



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP65

— Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions