

TECHNICAL CARD



LED Headlamp

VIDEX®



WARRANTY 3 YEARS

General parameters

Operation mode	TURBO, RED HIGH, RED LOW, RED FLASH, FLOOD HIGH, FLOOD MIDDLE, FLOOD LOW, SPOT HIGH, SPOT MIDDLE, SPOT LOW
Light source replaceable	no
Battery Warranty	1 year

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	20 W, 10 W
Input interface	USB-C

Photometric parameters

Useful luminous flux of the contained light source (Φuse)	2000 Lm
Correlated color temperature	5000K (neutral white), Red

VIDEX VLF-H066A 2000Lm 5000K

INDEX: VLF-H066A

Peak luminous intensity 4000 cd

Additional information

Housing colour	Black
Fall protection	2 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V, 3 V
Battery capacity	2200 mAh
Battery type	Li-ion 18650, CR123A (2pcs)
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP67
Housing material	Aviation anodized aluminum

Dimensions

EAN	4820246488143
In the package	1 pc.
Height	25.5 mm
Outer box	20 pcs.
Width	100 mm
Depth	34 mm
Unit nett weight	165g

Signs marking goods

VIDEX[®]

VIDEX VLF-H066A 2000Lm 5000K

INDEX: VLF-H066A

Packaging marking

CE, Utilization



VIDEX[®]

VIDEX VLF-H066A 2000Lm 5000K

INDEX: VLF-H066A

VIDEX[®]

VIDEX VLF-H066A 2000Lm 5000K

INDEX: VLF-H066A

VIDEX®

VIDEX VLF-H066A 2000Lm 5000K

INDEX: VLF-H066A

not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 2 meters



— The product is incompatible with light regulators



— Operating temperatures range



— The product does not contain mercury



— Class of protection against dust and moisture. The product has full protection against dust and short-term immersion in water up to a depth of 1 meter



We reserve the right to make technical changes. The data contained in this material is