

**VIDEX®**

VIDEX VLF-H085-OR 400Lm 5000K

**INDEX: VLF-H085-OR**

## TECHNICAL CARD



LED Headlamp



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

# VIDEX®



## WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrálno bijela / Neutralweiß / Alb neutru / Neutrus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

### General parameters

|                          |  |
|--------------------------|--|
| Operation mode           | HIGH, LOW, FLASH, COB + HIGH, COB HIGH, COB LOW, RED ON, RED FLASH |
| Light source replaceable | no   |

### Type of light source

|            |     |
|------------|-----|
| Dimmable   | no  |
| Technology | LED |

### Electrical parameters

|                     |               |
|---------------------|---------------|
| On-mode power (Pon) | 5 W + COB 5 W |
| Input interface     | USB-C         |

### Photometric parameters

|  |        |
|--|--------|
| Useful luminous flux of the contained light source (Φ <sub>use</sub> ) | 400 Lm |
|--|--------|

## VIDEX VLF-H085-OR 400Lm 5000K

### INDEX: VLF-H085-OR

|                              |                       |
|------------------------------|-----------------------|
| Correlated color temperature | 5000K (neutral white) |
| Peak luminous intensity      | 3000 cd               |

### Additional information

|                             |                  |
|-----------------------------|------------------|
| Housing colour              | Orange           |
| Fall protection             | 2 m              |
| Operating temperature range | -20° +40°C       |
| Battery type                | Li-pol           |
| Battery voltage             | 3.7 V            |
| Battery capacity            | 850 mAh          |
| Battery indicator           | 5 level          |
| Battery replaceable         | no               |
| Mercury content             | Does not contain |
| Ingress protection          | IP65             |
| Housing material            | Polyamide, Nylon |

### Dimensions

|                  |               |
|------------------|---------------|
| EAN              | 4820246484251 |
| Height           | 41 mm         |
| Depth            | 34 mm         |
| In the package   | 1 pc.         |
| Outer box        | 20 pcs.       |
| Width            | 50 mm         |
| Unit nett weight | 72g           |

# VIDEX®

VIDEX VLF-H085-OR 400Lm 5000K

INDEX: VLF-H085-OR

## Signs marking goods

Packaging marking

CE, Utilization



# VIDEX<sup>®</sup>

VIDEX VLF-H085-OR 400Lm 5000K

INDEX: VLF-H085-OR



**VIDEX<sup>®</sup>****VIDEX VLF-H085-OR 400Lm 5000K****INDEX: VLF-H085-OR**

# VIDEX®

VIDEX VLF-H085-OR 400Lm 5000K

INDEX: VLF-H085-OR



# VIDEX®

VIDEX VLF-H085-OR 400Lm 5000K

INDEX: VLF-H085-OR





# VIDEX®

## VIDEX VLF-H085-OR 400Lm 5000K

### INDEX: VLF-H085-OR



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 2 meters



— The product is incompatible with light regulators



— Operating temperatures range



— The product does not contain mercury



— Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions

Date: 30.08.2025