



**INDEX: VLE-P406W** 

# **TECHNICAL CARD**





**LED Panel** 







### VIDEX-PANEL-LED-40W-P406W-CW

#### **INDEX: VLE-P406W**









Free



Not Dimmable

Free

## **WARRANTY 3 YEARS**



Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / KaltweiB / Alb rece / Šalta balta / Auksti balta / Kűlm valge.

#### **General parameters**

Control gear replaceable	by the producer
Light source replaceable	by the producer

#### Type of light source

Energy class of the light source	D
Dimmable	no

#### **Electrical parameters**

Rated voltage, frequency	AC 175-265 V, 50/60 Hz
Rated current	300 mA
Input interface	Free wire ends
Electric shock protection class	II

#### **Photometric parameters**

Useful luminous flux of the light source (•use)	5200 Lm
Correlated color temperature	6000K (cold white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
Lifetime	30000 h
On/Off cycles	20000
Useful luminous flux of the light source reference	in a sphere (360°)

#### **Additional information**

Place of installation	Armstrong ceiling, Ceiling
Place of application	indoor
Housing colour	White
Diffuser material	Plastic
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum

#### **Dimensions**

EAN	5904405540633
Height	595 mm
Depth	10.8 mm



### VIDEX-PANEL-LED-40W-P406W-CW


#### **INDEX: VLE-P406W**

Width 595 mm
Outer box 5 pcs.









We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro Opt Sp. z o.o., Handlowa 23, 05-120 Legionowo, Poland.

Date: 8.09.2024