



**INDEX: VLE-P406W** 

# **TECHNICAL CARD**



**LED Panel** 













## VIDEX-PANEL-LED-40W-P406W-CW

## **INDEX: VLE-P406W**





















## **WARRANTY 3 YEARS**



Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / KaltweiB / Alb rece / Šalta balta / Auksti balta / Kűlm valge.

### **General parameters**

Light source or containing product	Containing product
Control gear replaceable	by the producer
Light source replaceable	by the producer

## Type of light source

Dimmable	no
Energy efficiency class of the contained light source	D

## **Electrical parameters**

Rated voltage, frequency	AC 175-265 V, 50/60 Hz
Rated current	300 mA
Input interface	Free wire ends

## **Photometric parameters**

**Electric shock protection class** 

Useful luminous flux of the contained light source (Фuse)	5200 Lm
Correlated color temperature	6000K (cold white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	30000 h
Useful luminous flux of the light source reference	in a sphere (360°)

#### **Additional information**

Place of installation	Armstrong ceiling, Ceiling
Place of application	indoor
Housing colour	White
Diffuser material	Plastic
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum

#### **Dimensions**

	5004405540000
EAN	5904405540633
In the package	1 pc.



## VIDEX-PANEL-LED-40W-P406W-CW

## **INDEX: VLE-P406W**

Height	595 mm
Outer box	5 pcs.
Width	595 mm
Depth	10.8 mm

## Signs marking goods


Packaging marking	Recycling of
	waste, CE,
	Utilization











We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

### VIDEX-PANEL-LED-40W-P406W-CW

#### **INDEX: VLE-P406W**



The product must be used indoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



Waste recycling after the end of the product's service





The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Rated beam angle



Ra > 80 – color rendering index



Rated On/off cycles



Nominal lifetime (hours)



The product does not emit ultraviolet light





The product is incompatible with light regulators



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. Protection against solid objects larger than 12 mm;

no protection against moisture

Date: 26.11.2025