

INDEX: VLE-P62-406W

TECHNICAL CARD



LED Panel







VIDEX-PANEL-LED-40W-P62-406W-CW

INDEX: VLE-P62-406W











Free









WARRANTY 3 YEARS



Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / KaltweiB / Alb rece / Šalta balta / Auksti balta / Kűlm valge.

General parameters

Light source or containing product	Containing product
Control gear replaceable	by the producer
Light source replaceable	by the producer

Type of light source

Dimmable	no
Energy efficiency class of the contained light source	D

Electrical parameters

Rated voltage, frequency	AC 175-265 V, 50/60 Hz
Rated current	300 mA
Input interface	Free wire ends

Photometric parameters

Electric shock protection class

Useful luminous flux of the contained light source (Фuse)	5200 Lm
Correlated color temperature	6000K (cold white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	30000 h
Useful luminous flux of the light source reference	in a sphere (360°)

Additional information

Place of installation	Armstrong ceiling, Ceiling
Place of application	indoor
Housing colour	White
Diffuser material	Plastic
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum

Dimensions

EAN	5904405540657
Outer box	5 pcs.



VIDEX-PANEL-LED-40W-P62-406W-CW


INDEX: VLE-P62-406W

Height	620 mm
Width	620 mm
Depth	10.8 mm









We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



VIDEX-PANEL-LED-40W-P62-406W-CW

4/4

INDEX: VLE-P62-406W



The product must be used indoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



— Rated beam angle



- Ra > 80 - color rendering index



— Rated On/off cycles



Nominal lifetime (hours)



— The product does not emit ultraviolet light



— The product is incompatible with light regulators



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture.

— Protection against solid objects larger than 12 mm; no protection against moisture

Date: 18.11.2025