

TECHNICAL CARD



LED Plant Grow Bulb



VIDEX®



360°



Ra ≥ 40



20 000 h

ON/OFF
20 000

Not Dimmable



No Flicker



Free



IP20

WARRANTY 2 YEARS

BICOLOR



1200K

Type of light source

Dimmable	no
Directional or non-directional light source	NDLS
Mains or non-mains light source	MLS
Colour-tuneable light source (CTLS)	-
Technology	LED

Electrical parameters

On-mode power (Pon)	8 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	70 mA
Displacement factor (cos φ1)	0.5
Survival factor	0.9

Photometric parameters

Correlated color temperature	1200K (bicolor)
-------------------------------------	--------------------

VIDEX-E27-A60-8W-FITO

INDEX: VLE-A60FF-08271

Beam angle	360°
Color rendering index (CRI)	Ra > 40
Lifetime	20000 h
On/Off cycles	20000
Useful luminous flux of the light source reference	in a sphere (360°)
Chromaticity coordinates (x)	0.485
Chromaticity coordinates (y)	0.427
R9 colour rendering index value	36
The lumen maintenance factor	≥94.8%
Flicker metric (Pst LM)	≤1
Stroboscopic effect metric (SVM)	≤0.4
CRI Min	-209
CRI Max	92

Additional information

Place of application	indoor
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP20

Dimensions

EAN	5904405540022
Height	105 mm
Width	60 mm
Depth	60 mm
Outer box	20 pcs.



VIDEX[®]

VIDEX-E27-A60-8W-FITO

INDEX: VLE-A60FF-08271

Unit nett weight 31g

In the package 1 pc.



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.

Date: 14.11.2024