

## TECHNICAL CARD



LED Portable Flashlight

# VIDEX®



## WARRANTY 3 YEARS



Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / Kaltweiß / Alb rece / Šalta balta / Auksti balta / Kūlm valge.

### General parameters

Operation mode	HIGH, LOW, STROBE
Light source replaceable	no

### Type of light source

Dimmable	no
Technology	LED

### Electrical parameters

On-mode power (Pon)	10 W
Input interface	USB-C

### Photometric parameters

Useful luminous flux of the contained light source (Φ <sub>use</sub> )	600 Lm
Correlated color temperature	5700K (cold white)
Peak luminous intensity	3320 cd

## VIDEX VLF-A055 600Lm 5700K

### INDEX: VLF-A055

### Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery type	Li-ion 16340
Battery voltage	3.7 V
Battery capacity	800 mAh
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP68
Housing material	Aviation anodized aluminum

### Dimensions

EAN	4820246481045
Height	74.5 mm
Depth	27 mm
Width	24 mm
In the package	1 pc.
Outer box	20 pcs.
Unit nett weight	44g

### Signs marking goods

Packaging marking	CE, Utilization
-------------------	-----------------

**VIDEX<sup>®</sup>**

VIDEX VLF-A055 600Lm 5700K


**INDEX: VLF-A055**

**VIDEX<sup>®</sup>****VIDEX VLF-A055 600Lm 5700K****INDEX: VLF-A055**

# VIDEX®

VIDEX VLF-A055 600Lm 5700K

INDEX: VLF-A055



**VIDEX®**  
MODEL | A055

ULTRACOMPACT RECHARGEABLE  
LED FLASHLIGHT



**600**  
MAX LUMENS



4  
LIGHTING  
MODES



TYPE-C



2m  
IP68



1m  
IMPACT  
RESISTANCE

**VIDEX®**  
MODEL | A055




LUMINUS SST20  
10W  
5700K

Energy efficient led provides maximum output 600 lumens,  
beam distance 115m and long service life up to 50000 hours.

# VIDEX®

VIDEX VLF-A055 600Lm 5700K

INDEX: VLF-A055





# VIDEX®

VIDEX VLF-A055 600Lm 5700K

INDEX: VLF-A055



# VIDEX®

## VIDEX VLF-A055 600Lm 5700K

### INDEX: VLF-A055

**VIDEX®**  
MODEL | A055



High-quality copper conducts current better and retains elasticity over the years compared to cheaper metals.

**VIDEX®**  
MODEL | A055



**WITH BATTERY 800mAh**

	HIGH	LOW	MOON	STROBE
OUTPUT	600 Lm	150 Lm	30 Lm	600 Lm
RUNTIME	1h 40min	2h 45min	13h	1h 40min
DISTANCE	115m	54m	20m	115m
INTENSITY	3320cd	640cd	300cd	3320cd

Protection against over charge, over discharge, wrong polarity.

**VIDEX®**  
MODEL | A055

PROGRAM ROOT



Start position	Action A	Result	Action B	Result
OFF	Click	> ON > HIGH > LOW > MOON > STROBE > OFF >		
** HIGH / LOW / MOON / STROBE	Press and hold for 0.5 sec	OFF **	Press and hold for 0.5 sec	ON **

\*\* The current mode memorized and applied next time when turned on.  
Note: Battery indication is always on if the light is switched on.

**VIDEX®**  
MODEL | A055

KIT CONTENT



SPARE SILICONE RINGS

USER'S MANUAL, WARRANTY CARD    LI-ION BATTERY    FLASHLIGHT    LANYARD    CHARGING CABLE

SIZE 74.5x24x27mm  
WEIGHT 44g (without battery)

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



## INDEX: VLF-A055



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 1 meter



Not Dimmable

— The product is incompatible with light regulators



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP68

— Class of protection against dust and moisture.  
The product has full protection against dust and prolonged immersion in water at a depth of more than 1 meter