

**VIDEX<sup>®</sup>**

VIDEX VLF-A055 600Lm 5700K

**INDEX: VLF-A055**

## TECHNICAL CARD



LED Portable Flashlight



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

# VIDEX®



## WARRANTY 3 YEARS

### COLD WHITE



### 5700K

Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / Kaltweiß / Alb rece / Šalta balta / Auksti balta / Kúlm valge.

## General parameters

**Light source replaceable** no

## Type of light source

**Dimmable** no

**Technology** LED

## Electrical parameters

**On-mode power (Pon)** 10 W

**Input interface** USB-C

## Photometric parameters

**Useful luminous flux of the contained light source ( $\Phi_{use}$ )** 600 Lm

**Correlated color temperature** 5700K (cold white)

**Peak luminous intensity** 3320 cd

## Additional information

## VIDEX VLF-A055 600Lm 5700K

### INDEX: VLF-A055

<b>Housing colour</b>	Black
<b>Fall protection</b>	1 m
<b>Operating temperature range</b>	-20° +40°C
<b>Mercury content</b>	Does not contain
<b>Ingress protection</b>	IP68
<b>Housing material</b>	Aviation anodized aluminum

## Dimensions

<b>EAN</b>	4820246481045
<b>Height</b>	74.5 mm
<b>Width</b>	24 mm
<b>Depth</b>	27 mm
<b>In the package</b>	1 pc.
<b>Outer box</b>	20 pcs.
<b>Unit nett weight</b>	44g

## Signs marking goods

**Packaging marking** CE, Utilization

**VIDEX<sup>®</sup>**

VIDEX VLF-A055 600Lm 5700K

**INDEX: VLF-A055**

**VIDEX®**


VIDEX VLF-A055 600Lm 5700K

**INDEX: VLF-A055**

# VIDEX®

VIDEX VLF-A055 600Lm 5700K

INDEX: VLF-A055



**VIDEX®**  
MODEL | **A055**

ULTRACOMPACT RECHARGEABLE  
LED FLASHLIGHT



**600**  
MAX LUMENS

- 4 LIGHTING MODES
- TYPE-C
- 2m IP68
- 1m IMPACT RESISTANCE

**VIDEX®**  
MODEL | **A055**



LUMINUS SST20  
10W  
5700K

Energy efficient led provides maximum output 600 lumens, beam distance 115m and long service life up to 50000 hours.

# VIDEX®

## VIDEX VLF-A055 600Lm 5700K

### INDEX: VLF-A055



# VIDEX®

VIDEX VLF-A055 600Lm 5700K

INDEX: VLF-A055

**VIDEX®** IP68 WATER RESISTANCE  
MODEL | **A055**



Protection against dust and moisture IP68 allows short-term submersions under water to a depth of up to two meters.

**VIDEX®**  
MODEL | **A055**



Built-in type-c port for direct charging. Charging time around 2.5 hours.

**VIDEX®**  
MODEL | **A055**



Construction includes loop for a wrist lanyard. The flashlight will always be at hand.

**VIDEX®** METAL CLIP  
MODEL | **A055**



For convenient attachment of the flashlight to pocket, belt or backpack.

# VIDEX®

## VIDEX VLF-A055 600Lm 5700K

### INDEX: VLF-A055

**VIDEX®**  
MODEL | A055



High-quality copper conducts current better and retains elasticity over the years compared to cheaper metals.

**VIDEX®**  
MODEL | A055



**WITH BATTERY 800mAh**

	HIGH	LOW	MOON	STROBE
OUTPUT	600 Lm	150 Lm	30 Lm	600 Lm
RUNTIME	1h 40min	2h 45min	13h	1h 40min
DISTANCE	115m	54m	20m	115m
INTENSITY	3320cd	640cd	300cd	3320cd

Protection against over charge, over discharge, wrong polarity.

**VIDEX®**  
MODEL | A055

PROGRAM ROOT



\*\* The current mode memorized and applied next time when turned on.  
Note. Battery indication is always on if the light is switched on.

**VIDEX®**  
MODEL | A055

KIT CONTENT

SPARE SILICONE RINGS



USER'S MANUAL, WARRANTY CARD    LI-ION BATTERY    FLASHLIGHT    LANYARD    CHARGING CABLE

SIZE 74.5x24x27mm  
WEIGHT 44g (without battery)

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.

Date: 23.02.2025