

VIDEX®

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H

TECHNICAL CARD



LED Portable Flashlight



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



WARRANTY 3 YEARS

COLD WHITE



5700K

Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / Kaltweiß / Alb rece / Šalta balta / Auksti balta / Kúlm valge.

General parameters

Light source replaceable no

Type of light source

Dimmable no

Technology LED

Electrical parameters

On-mode power (Pon) 10 W

Input interface USB-C

Photometric parameters

Useful luminous flux of the light source (Φ_{use}) 600 Lm

Correlated color temperature 5700K (cold white)

Peak luminous intensity 3320 cd

Additional information

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP68
Housing material	Aviation anodized aluminum

Dimensions

EAN	4820246481038
Height	74.5 mm
Width	24 mm
Depth	27 mm
Outer box	20 pcs.
Unit nett weight	79g
In the package	1 pc.

Signs marking goods

Packaging marking CE, Utilization

VIDEX®

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H

VIDEX[®]

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H

VIDEX®

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H



VIDEX®

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H

VIDEX®
MODEL | A055H

HIGH UTILITY ULTRACOMPACT
RECHARGEABLE LED FLASHLIGHT



600
MAX LUMENS

- HEAD&HAND USE
- TYPE-C
- 2m IP68
- 1m IMPACT RESISTANCE

VIDEX®
MODEL | A055H

LUMINUS SST
10W 5700K



Energy efficient led provides maximum output 600 lumens, beam distance 115m and long service life up to 50000 hours.

VIDEX®
MODEL | A055H

TEXTURED REFLECTOR



New textured reflector provides a wider illumination area.

VIDEX®
MODEL | A055H

TEMPERED GLASS



Textured reflector for even light distribution. Tempered glass is more resistant to scratches, high temperatures and has better light transmission properties.

INDEX: VLF-A055H



INDEX: VLF-A055H



VIDEX®

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.