

VIDEX[®]

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H

TECHNICAL CARD



LED Portable Flashlight



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



Not Dimmable



Free



IP68

WARRANTY 3 YEARS

COLD WHITE



5700K

Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / Kaltweiß / Alb rece / Šalta balta / Auksti balta / Kúlm valge.

General parameters

Light source replaceable no

Type of light source

Dimmable no

Technology LED

Electrical parameters

On-mode power (Pon) 10 W

Input interface USB-C

Photometric parameters

Useful luminous flux of the light source (Φ_{use}) 600 Lm

Correlated color temperature 5700K (cold white)

Peak luminous intensity 3320 cd

Additional information

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H

| | |
|------------------------------------|----------------------------|
| Housing colour | Black |
| Operating temperature range | -20° +40°C |
| Mercury content | Does not contain |
| Ingress protection | IP68 |
| Housing material | Aviation anodized aluminum |

Dimensions

| | |
|-------------------------|---------------|
| EAN | 4820246481038 |
| Height | 74.5 mm |
| Width | 24 mm |
| Depth | 27 mm |
| Outer box | 20 pcs. |
| Unit nett weight | 79g |
| In the package | 1 pc. |

Signs marking goods

Packaging marking CE, Utilization

VIDEX[®]

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H

VIDEX[®]

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H

VIDEX®

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H



VIDEX®

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H

VIDEX®
MODEL | A055H

HIGH UTILITY ULTRACOMPACT
RECHARGEABLE LED FLASHLIGHT



600
MAX LUMENS

- HEAD&HAND USE
- TYPE-C
- 2m IP68
- 1m IMPACT RESISTANCE

VIDEX®
MODEL | A055H

LUMINUS SST
10W 5700K



Energy efficient led provides maximum output 600 lumens, beam distance 115m and long service life up to 50000 hours.

VIDEX®
MODEL | A055H

TEXTURED REFLECTOR



New textured reflector provides a wider illumination area.

VIDEX®
MODEL | A055H

TEMPERED GLASS



Textured reflector for even light distribution. Tempered glass is more resistant to scratches, high temperatures and has better light transmission properties.

INDEX: VLF-A055H



INDEX: VLF-A055H



VIDEX®

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro Opt Sp. z o.o., Handlowa 23, 05-120 Legionowo, Poland.