

**VIDEX®**

VIDEX VLF-A055H 600Lm 5700K

**INDEX: VLF-A055H**

## TECHNICAL CARD



LED Portable Flashlight



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

# VIDEX®



## WARRANTY 3 YEARS

COLD WHITE



5700K

Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / Kaltweiß / Alb rece / Šalta balta / Auksti balta / Kūlm valge.

### General parameters

Operation mode	HIGH, LOW, STROBE
Light source replaceable	no
Battery Warranty	1 year

### Type of light source

Dimmable	no
Technology	LED

### Electrical parameters

On-mode power (Pon)	10 W
Input interface	USB-C

### Photometric parameters

Useful luminous flux of the contained light source (Φ <sub>use</sub> )	600 Lm
Correlated color temperature	5700K (cold white)

VIDEX VLF-A055H 600Lm 5700K

### INDEX: VLF-A055H

Peak luminous intensity 3320 cd

### Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V
Battery capacity	800 mAh
Battery type	Li-ion 16340
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP68
Housing material	Aviation anodized aluminum

### Dimensions

EAN	4820246481038
In the package	1 pc.
Outer box	20 pcs.
Height	74.5 mm
Width	24 mm
Depth	27 mm
Unit nett weight	79g

### Signs marking goods

Packaging marking CE, Utilization

# VIDEX®

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H



**VIDEX<sup>®</sup>**

VIDEX VLF-A055H 600Lm 5700K

**INDEX: VLF-A055H**

# VIDEX®

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H



# VIDEX®

## VIDEX VLF-A055H 600Lm 5700K

### INDEX: VLF-A055H

**VIDEX®**  
MODEL | A055H

HIGH UTILITY ULTRACOMPACT  
RECHARGEABLE LED FLASHLIGHT



**600**  
MAX LUMENS

HEAD&HAND  
USE

TYPE-C

2m  
IP68

1m  
IMPACT  
RESISTANCE

**VIDEX®**  
MODEL | A055H

LUMINUS SST  
10W 5700K



Energy efficient led provides maximum output 600 lumens,  
beam distance 115m and long service life up to 50000 hours.

**VIDEX®**  
MODEL | A055H

TEXTURED REFLECTOR



New textured reflector provides  
a wider illumination area.

**VIDEX®**  
MODEL | A055H

TEMPERED GLASS



Textured reflector for even light distribution.  
Tempered glass is more resistant to scratches, high temperatures  
and has better light transmission properties.

### INDEX: VLF-A055H



INDEX: VLF-A055H





VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

PROGRAM ROOT

MODEL **A055H**

Start position	Action A	Result	Action B	Result
OFF	Click	> ON > HIGH > LOW > MOON > STROBE > OFF >		
** HIGH / LOW / MOON / STROBE	Press and hold for 0.5 sec.	OFF **	Press and hold for 0.5 sec.	ON **

\*\* The current mode memorized and applied next time when turned on.  
 Note. Battery indication is always on if the light is switched on.

---

KIT CONTENT

MODEL **A055H**

USER'S MANUAL,  
WARRANTY CARD.

CHARGING  
CABLE

LI-ION  
BATTERY

FLASHLIGHT

HEADBAND

SPARE SILICONE  
RINGS

FAST RELEASE  
HEAD HOLDER

SIZE 74.5x23x27mm  
 WEIGHT 79g (with headband, without battery)

- The product meets the requirements of EU directives
- It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste
- The protection is effective in case of a fall from a height of up to 1 meter
- The product is incompatible with light regulators
- Operating temperatures range
- The product does not contain mercury
- Class of protection against dust and moisture. The product has full protection against dust and prolonged immersion in water at a depth of more than 1 meter