

TECHNICAL CARD



LED Portable Flashlight

VIDEX®



WARRANTY 3 YEARS



Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / Kaltweiß / Alb rece / Šalta balta / Auksti balta / Kūlm valge.

General parameters

Operation mode	HIGH, LOW, STROBE
Light source replaceable	no
Battery Warranty	1 year

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	10 W
Input interface	USB-C

Photometric parameters

Useful luminous flux of the contained light source (Φ _{use})	600 Lm
Peak luminous intensity	3320 cd

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H

Correlated color temperature 5700K (cold white)

Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V
Battery type	Li-ion 16340
Battery capacity	800 mAh
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP68
Housing material	Aviation anodized aluminum

Dimensions

EAN	4820246481038
In the package	1 pc.
Height	74.5 mm
Outer box	20 pcs.
Width	24 mm
Depth	27 mm
Unit nett weight	79g

Signs marking goods

Packaging marking	CE, Utilization
-------------------	-----------------

VIDEX®

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H



VIDEX[®]

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H

VIDEX[®]

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H

VIDEX®

VIDEX VLF-A055H 600Lm 5700K

INDEX: VLF-A055H

VIDEX®
MODEL | A055H

HIGH UTILITY ULTRACOMPACT
RECHARGEABLE LED FLASHLIGHT



600
MAX LUMENS

HEAD&HAND
USE

TYPE-C

2m
IP68

1m
IMPACT
RESISTANCE

VIDEX®
MODEL | A055H

LUMINUS SST
10W 5700K



Energy efficient led provides maximum output 600 lumens,
beam distance 115m and long service life up to 50000 hours.

VIDEX®
MODEL | A055H

TEXTURED REFLECTOR



New textured reflector provides
a wider illumination area.

VIDEX®
MODEL | A055H

TEMPERED GLASS



Textured reflector for even light distribution.
Tempered glass is more resistant to scratches, high temperatures
and has better light transmission properties.

INDEX: VLF-A055H



INDEX: VLF-A055H

VIDEX®
MODEL | **A055H**

IP68 WATER RESISTANCE



Protection against dust and moisture IP68 allows short-term submersions under water to a depth of up to two meters.

VIDEX®
MODEL | **A055H**



High-quality copper conducts current better and retains elasticity over the years compared to cheaper metals.

VIDEX®
MODEL | **A055H**

METAL CLIP



For convenient attachment of the flashlight to pocket, belt or backpack.

VIDEX®
MODEL | **A055H**



WITH BATTERY 800mAh

	HIGH	LOW	MOON	STROBE
OUTPUT	600 Lm	150 Lm	30 Lm	600 Lm
RUNTIME	1h 40min	2h 45min	13h	1h 40min
DISTANCE	115m	54m	20m	115m
INTENSITY	3320cd	740cd	300cd	3320cd

Protection against over charge, over discharge, wrong polarity.

INDEX: VLF-A055H

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.


PROGRAM ROOT

MODEL **A055H**



Start position	Action A	Result	Action B	Result
OFF	Click	> ON > HIGH > LOW > MOON > STROBE > OFF >		
** HIGH / LOW / MOON / STROBE	Press and hold for 0.5 sec.	OFF **	Press and hold for 0.5 sec.	ON **

** The current mode memorized and applied next time when turned on.
 Note. Battery indication is always on if the light is switched on.


KIT CONTENT

MODEL **A055H**



USER'S MANUAL,
WARRANTY CARD.



CHARGING
CABLE



LI-ION
BATTERY



FLASHLIGHT



HEADBAND



FAST RELEASE
HEAD HOLDER



SPARE SILICONE
RINGS

SIZE 74.5x23x27mm
 WEIGHT 79g (with headband, without battery)



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



The protection is effective in case of a fall from a height of up to 1 meter



The product is incompatible with light regulators



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. The product has full protection against dust and prolonged immersion in water at a depth of more than 1 meter