

VIDEX®

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH

TECHNICAL CARD



LED Portable Flashlight



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



WARRANTY 3 YEARS

NEUTRAL WHITE



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevturalno bela / Nevturalno bijela / Neutralweiß / Alb neutru / Nevturalus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

General parameters

Light source replaceable	no
---------------------------------	----

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	10 W
Input interface	USB-C

Photometric parameters

Useful luminous flux of the light source (Φ_{use})	1200 Lm
Correlated color temperature	5000K (neutral white)
Peak luminous intensity	5200 cd

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH

Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP66
Housing material	Aviation anodized aluminum

Dimensions

EAN	4820246481007
Height	127 mm
Width	28 mm
Depth	28 mm
In the package	1 pc.
Outer box	20 pcs.
Unit nett weight	83g

Signs marking goods

Packaging marking	CE, Utilization
--------------------------	-----------------

VIDEX®

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH

VIDEX[®]

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH

VIDEX®

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH



VIDEX®
MODEL | A105RH

MULTITASKING RECHARGEABLE
LED FLASHLIGHT

1200
MAX LUMENS

- SWIVEL HEAD
- TYPE-C
- IP66
- 1m IMPACT RESISTANCE

VIDEX®

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH



VIDEX®

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH



VIDEX®

MODEL | A105RH

VIDEX®

MODEL | A105RH

ANODIZED METAL SWITCH



Switch on/off the light, select the modes, and lock the flashlight. Press and hold for quick access to strobe mode. The flashlight's scheme memorizes the previously selected lighting mode (except strobe mode) and applies it at a next power-on.



VIDEX®

MODEL | A105RH

VIDEX®

MODEL | A105RH

INTEGRATED FOUR-LEVEL LED BATTERY INDICATOR

Water resistance IP66 gives reliable protection from any precipitation.



CHARGE
100-85%



CHARGE
85-50%



CHARGE
50-25%



CHARGE
25-1%

VIDEX®

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH



VIDEX®

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH

VIDEX®
MODEL A105RH



Scratch resistant tempered glass lens easily stands against high temperatures.

VIDEX®
MODEL A105RH



Copper-made springs keep flexible over the years and guarantee a firm contact.

VIDEX®
MODEL A105RH



WITH BATTERY 2200mAh

	TURBO	HIGH	MIDDLE	LOW	MOON	SOS
OUTPUT	1200 Lm	700 Lm	420 Lm	220 Lm	30 Lm	700 Lm
RUNTIME	1h*	1h 30min	2h 35min	5h 40min	80h	2h
DISTANCE	135m	104m	80m	57m	30m	104m
INTENSITY	5200cd	2680cd	1608cd	816cd	300cd	2680cd

The above output parameters tested with the stock battery Videx 18650 2200mAh and may vary due to conditions and actual batteries used.
*Turbo mode output levels may be reduced by the overheat control system.

VIDEX® PROGRAM ROOT
MODEL A105RH



Start position	Action A	Result	Action B	Result
OFF	Press and hold for 0.5 sec	ON	Press and hold for 0.5 sec	OFF
ON	Click	> MOON > LOW > MIDDLE > HIGH > TURBO >		
ON/OFF	Press and hold for 3 sec	STROBE	Click	Exit
OFF	Click	Battery status		
OFF	Double click	Lock	Double click	Unlock

Notes: The flashlight automatically memorizes the last selected lighting mode (excluding Strobe mode) and applies it next time when turned on. Battery indication is always on if the light is switched on.

VIDEX[®]

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.