

VIDEX[®]

VIDEX VLF-A105Z 1200Lm 5000K

INDEX: VLF-A105Z

TECHNICAL CARD



LED Portable Flashlight



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



WARRANTY 3 YEARS

NEUTRAL WHITE



5000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevturalno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutrus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

General parameters

Light source replaceable	no
---------------------------------	----

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	10 W
Input interface	USB-C

Photometric parameters

Useful luminous flux of the light source (Φuse)	1200 Lm
Correlated color temperature	5000K (neutral white)
Peak luminous intensity	11600 cd

VIDEX VLF-A105Z 1200Lm 5000K

INDEX: VLF-A105Z

Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP44
Housing material	Aviation anodized aluminum

Dimensions

EAN	4820246481021
Height	140 mm
Width	29 mm
Depth	29 mm
Outer box	20 pcs.
Unit nett weight	99g
In the package	1 pc.

Signs marking goods

Packaging marking	CE, Utilization
--------------------------	-----------------

VIDEX[®]

VIDEX VLF-A105Z 1200Lm 5000K

INDEX: VLF-A105Z

VIDEX[®]

VIDEX VLF-A105Z 1200Lm 5000K

INDEX: VLF-A105Z

VIDEX[®]

VIDEX VLF-A105Z 1200Lm 5000K

INDEX: VLF-A105Z

VIDEX®

VIDEX VLF-A105Z 1200Lm 5000K

INDEX: VLF-A105Z



VIDEX®
MODEL | A105Z

ZOOMABLE RECHARGEABLE
FLASHLIGHT

1200
LUMENS

ZOOM TYPE-C IP44 1m IMPACT RESISTANCE

A composite image featuring the flashlight in a natural setting on a green fabric, a product information box with the VIDEX logo and model number, and a flashlight with its light on against a dark background. At the bottom, there are icons for Zoom, Type-C, IP44, and 1m Impact Resistance, along with the text '1200 LUMENS'.

VIDEX®

VIDEX VLF-A105Z 1200Lm 5000K

INDEX: VLF-A105Z



INDEX: VLF-A105Z

VIDEX®
MODEL | A105Z

SIDE SWITCH



For quick selection of lighting modes. Made of anodized metal, with good tactile feedback.

MOON | LOW | MIDDLE | HIGH | TURBO | STROBE
(press and hold the side switch).

VIDEX®
MODEL | A105Z



The design provides a loop for attaching the wrist strap.

VIDEX®
MODEL | A105Z

DETACHEABLE METAL CLIP



ANTI-ROLL BODY CONSTRUCTION

Detachable metal clip. Conveniently hang the flashlight on pocket, belt or backpack.

VIDEX®
MODEL | A105Z

INTEGRATED FOUR-LEVEL LED BATTERY INDICATOR



CHARGE 100-85%	CHARGE 85-50%	CHARGE 50-25%	CHARGE 25-1%

VIDEX®

VIDEX VLF-A105Z 1200Lm 5000K

INDEX: VLF-A105Z



IP44 moisture and dust resistance. Rain protection.



High-quality copper conducts current better and retains elasticity over the years compared to cheaper metals.



The new TYPE-C charging port is protected from dust and water by a silicone cap. The battery indicator displays appropriate charging status.

WITH BATTERY 2200mAh

	TURBO	HIGH	MIDDLE	LOW	MOON	SOS
OUTPUT	1200 Lm	650 Lm	425 Lm	260 Lm	30 Lm	650 Lm
RUNTIME	1h 30min*	1h 40min	2h 30min	5h 20min	83h	1h 40min
DISTANCE	215m	156m	130m	104m	35m	156m
INTENSITY	11600cd	6096cd	4200cd	2720cd	312cd	6096cd

The above output parameters tested with the stock battery Videx 18650 2200mAh and may vary due to conditions and actual batteries used.
*Turbo mode output levels may be reduced by the overheat control system.

VIDEX®

VIDEX VLF-A105Z 1200Lm 5000K

INDEX: VLF-A105Z



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.