

VIDEX®

VIDEX VLF-A156R 1700Lm 6500K

INDEX: VLF-A156R

TECHNICAL CARD



LED Portable Flashlight



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



Not Dimmable



Free



IP68

WARRANTY 3 YEARS

COLD WHITE



6500K

Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / Kaltweiß / Alb rece / Šalta balta / Auksti balta / Kúlm valge.

General parameters

Light source replaceable no

Type of light source

Dimmable no

Technology LED

Electrical parameters

On-mode power (Pon) 20 W

Input interface USB-C

Photometric parameters

Useful luminous flux of the light source (Φ_{use}) 1700 Lm

Correlated color temperature 6500K (cold white)

Peak luminous intensity 10960 cd

Additional information

VIDEX VLF-A156R 1700Lm 6500K

INDEX: VLF-A156R

Housing colour	Black
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP68
Housing material	Aviation anodized aluminum

Dimensions

EAN	4820246480994
Height	131 mm
Width	31 mm
Depth	31 mm
Outer box	20 pcs.
Unit nett weight	85g
In the package	1 pc.

Signs marking goods

Packaging marking CE, Utilization

INDEX: VLF-A156R



VIDEX[®]

VIDEX VLF-A156R 1700Lm 6500K

INDEX: VLF-A156R

VIDEX®

VIDEX VLF-A156R 1700Lm 6500K

INDEX: VLF-A156R



VIDEX®
MODEL | A156R

RECHARGEABLE LED FLASHLIGHT

1700
MAX LUMENS

- ROTARY SWITCH
- TYPE-C
- IP68
- 1m IMPACT RESISTANCE

VIDEX®
MODEL | A156R

ROTARY SWITCH

With the significant tactile click when turning the switch and contrasting markings, it is convenient to find the desired lighting mode.

VIDEX®

VIDEX VLF-A156R 1700Lm 6500K

INDEX: VLF-A156R



VIDEX®

VIDEX VLF-A156R 1700Lm 6500K

INDEX: VLF-A156R





VIDEX VLF-A156R 1700Lm 6500K

INDEX: VLF-A156R

VIDEX®
MODEL | A156R



WITH BATTERY 4000mAh

	TURBO	HIGH	MIDDLE	LOW	STROBE
OUTPUT	1700 Lm	770 Lm	480 Lm	160 Lm	770 Lm
RUNTIME	2h 45min*	3h	5h	17h 50min	4h 45min
DISTANCE	210m	155m	135m	87m	155m
INTENSITY	10960cd	6000cd	4560cd	1900cd	6000cd

The above output parameters tested with the stock battery Videx 21700 4000mAh and may vary due to conditions and actual batteries used.
*Turbo mode output levels may be reduced by the overheat control system.

VIDEX® PROGRAM ROOT
MODEL | A156R



```

    graph LR
      Start[Start position: OFF] --> Action[Action A: Turn right]
      Action --> Result[Result: ON LOW > MIDDLE > HIGH > TURBO > STROBE]
  
```

Note: Battery indication is always on if the light is switched on.

VIDEX® KIT CONTENT
MODEL | A156R



- USER'S MANUAL, WARRANTY CARD.
- LI-ION BATTERY 4000MAH
- FLASHLIGHT
- LANYARD
- CHARGING CABLE
- SPARE SILICONE RINGS

SIZE 131x31mm
WEIGHT 85g (without battery)

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro Opt Sp. z o.o., Handlowa 23, 05-120 Legionowo, Poland.