

VIDEX[®]

VIDEX VLF-A156R 1700Lm 6500K

INDEX: VLF-A156R

TECHNICAL CARD



LED Portable Flashlight



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



WARRANTY 3 YEARS

COLD WHITE



6500K

Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / Kaltweiß / Alb rece / Šalta balta / Auksti balta / Kúlm valge.

General parameters

| | |
|--------------------------|----------------------------------|
| Operation mode | TURBO, HIGH, MIDDLE, LOW, STROBE |
| Light source replaceable | no |
| Battery Warranty | 1 year |

Type of light source

| | |
|------------|-----|
| Dimmable | no |
| Technology | LED |

Electrical parameters

| | |
|---------------------|-------|
| On-mode power (Pon) | 20 W |
| Input interface | USB-C |

Photometric parameters

| | |
|--|--------------------|
| Useful luminous flux of the contained light source (Φ _{use}) | 1700 Lm |
| Correlated color temperature | 6500K (cold white) |

VIDEX VLF-A156R 1700Lm 6500K

INDEX: VLF-A156R

Peak luminous intensity 10960 cd

Additional information

| | |
|-----------------------------|----------------------------|
| Housing colour | Black |
| Fall protection | 1 m |
| Operating temperature range | -20° +40°C |
| Battery voltage | 3.7 V |
| Battery capacity | 4000 mAh |
| Battery type | Li-ion 21700, Li-ion 18650 |
| Battery indicator | 4 level |
| Battery replaceable | yes |
| Mercury content | Does not contain |
| Ingress protection | IP68 |
| Housing material | Aviation anodized aluminum |

Dimensions

| | |
|------------------|---------------|
| EAN | 4820246480994 |
| In the package | 1 pc. |
| Outer box | 20 pcs. |
| Height | 131 mm |
| Width | 31 mm |
| Depth | 31 mm |
| Unit nett weight | 85g |

Signs marking goods

Packaging marking CE, Utilization

VIDEX®

VIDEX VLF-A156R 1700Lm 6500K

INDEX: VLF-A156R

VIDEX[®]

VIDEX VLF-A156R 1700Lm 6500K

INDEX: VLF-A156R

VIDEX®

VIDEX VLF-A156R 1700Lm 6500K

INDEX: VLF-A156R



VIDEX®
MODEL | A156R

RECHARGEABLE LED FLASHLIGHT

1700
MAX LUMENS

ROTARY SWITCH TYPE-C IP68 1m IMPACT RESISTANCE

VIDEX®
MODEL | A156R

ROTARY SWITCH

With the significant tactile click when turning the switch and contrasting markings, it is convenient to find the desired lighting mode.

VIDEX®

VIDEX VLF-A156R 1700Lm 6500K

INDEX: VLF-A156R



VIDEX®

VIDEX VLF-A156R 1700Lm 6500K

INDEX: VLF-A156R



VIDEX®

VIDEX VLF-A156R 1700Lm 6500K

INDEX: VLF-A156R

VIDEX®
MODEL | A156R



WITH BATTERY 4000mAh

| | TURBO | HIGH | MIDDLE | LOW | STROBE |
|-----------|-----------|--------|--------|-----------|----------|
| OUTPUT | 1700 Lm | 770 Lm | 480 Lm | 160 Lm | 770 Lm |
| RUNTIME | 2h 45min* | 3h | 5h | 17h 50min | 4h 45min |
| DISTANCE | 210m | 155m | 135m | 87m | 155m |
| INTENSITY | 10960cd | 6000cd | 4560cd | 1900cd | 6000cd |

The above output parameters tested with the stock battery Videx 21700 4000mAh and may vary due to conditions and actual batteries used.
*Turbo mode output levels may be reduced by the overheat control system.

VIDEX® PROGRAM ROOT
MODEL | A156R



Note: Battery indication is always on if the light is switched on.

VIDEX® KIT CONTENT
MODEL | A156R



SPARE SILICONE RINGS

USER'S MANUAL, WARRANTY CARD. LI-ION BATTERY 4000MAH. FLASHLIGHT. LANYARD. CHARGING CABLE.

SIZE 131x31mm
WEIGHT 85g (without battery)

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



The protection is effective in case of a fall from a height of up to 1 meter



The product is incompatible with light regulators



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. The product has full protection against dust and prolonged immersion in water at a depth of more than 1 meter

Date: 4.06.2026