

TECHNICAL CARD



LED Portable Flashlight

VIDEX®



WARRANTY 3 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálina biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrálno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Operation mode	TURBO, HIGH, MIDDLE, LOW, MOON, RED HIGH, RED LOW, RED FLASH
Light source replaceable	no

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	10 W
Input interface	USB-C

Photometric parameters

Useful luminous flux of the contained light source (Φ _{use})	1000 Lm
--	---------

VIDEX VLF-A232R 1000Lm 5000K

INDEX: VLF-A232R

Correlated color temperature	5000K (neutral white)
Peak luminous intensity	5250 cd

Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery type	Li-ion 18650
Battery voltage	3.7 V
Battery capacity	2200 mAh
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP66
Housing material	Anodized aluminum

Dimensions

EAN	4820246486774
Height	118 mm
Depth	25 mm
Width	25 mm
In the package	1 pc.
Outer box	20 pcs.
Unit nett weight	78g

VIDEX[®]

VIDEX VLF-A232R 1000Lm 5000K

INDEX: VLF-A232R**Signs marking goods****Packaging marking**

CE, Utilization



VIDEX®

VIDEX VLF-A232R 1000Lm 5000K

INDEX: VLF-A232R



VIDEX[®]**VIDEX VLF-A232R 1000Lm 5000K****INDEX: VLF-A232R**

VIDEX®**VIDEX VLF-A232R 1000Lm 5000K****INDEX: VLF-A232R**

VIDEX®

VIDEX VLF-A232R 1000Lm 5000K

INDEX: VLF-A232R



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 1 meter



Not Dimmable

— The product is incompatible with light regulators



-20° - +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP66

— Class of protection against dust and moisture. The product has full protection against dust and powerful water jets

Date: 31.05.2025