

TECHNICAL CARD



LED Portable Flashlight

VIDEX®



WARRANTY 3 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálina biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrálno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

General parameters

| | |
|--------------------------|--|
| Operation mode | TURBO, MIDDLE, LOW, MOON, RED HIGH, RED LOW, RED FLASH |
| Light source replaceable | no |
| Battery Warranty | 1 year |

Type of light source

| | |
|------------|-----|
| Dimmable | no |
| Technology | LED |

Electrical parameters

| | |
|---------------------|-------|
| On-mode power (Pon) | 10 W |
| Input interface | USB-C |

Photometric parameters

VIDEX VLF-A244RH 600Lm 5000K

INDEX: VLF-A244RH

| | |
|---|-----------------------|
| Useful luminous flux of the contained light source (Φuse) | 600 Lm |
| Correlated color temperature | 5000K (neutral white) |
| Peak luminous intensity | 2800 cd |

Additional information

| | |
|-----------------------------|----------------------------|
| Housing colour | Black |
| Fall protection | 1 m |
| Operating temperature range | -20° +40°C |
| Battery type | Li-ion 16340 |
| Battery voltage | 3.7 V |
| Battery capacity | 800 mAh |
| Battery indicator | 4 level |
| Battery replaceable | yes |
| Mercury content | Does not contain |
| Ingress protection | IP66 |
| Housing material | Aviation anodized aluminum |

Dimensions

| | |
|------------------|---------------|
| EAN | 4820246484220 |
| Height | 87.4 mm |
| Depth | 22.5 mm |
| Width | 23 mm |
| In the package | 1 pc. |
| Outer box | 20 pcs. |
| Unit nett weight | 59g |

VIDEX®

VIDEX VLF-A244RH 600Lm 5000K

INDEX: VLF-A244RH**Signs marking goods****Packaging marking**

CE, Utilization



VIDEX®

VIDEX VLF-A244RH 600Lm 5000K

INDEX: VLF-A244RH



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 1 meter

— The product is incompatible with light regulators

— Operating temperatures range

— The product does not contain mercury

— Class of protection against dust and moisture. The product has full protection against dust and powerful water jets

Date: 25.06.2025