

INDEX: VLF-A244RH

TECHNICAL CARD



LED Portable Flashlight



VIDEX VLF-A244RH 600Lm 5000K

INDEX: VLF-A244RH

















Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Operation mode	TURBO, MIDDLE, LOW, MOON, RED HIGH, RED LOW, RED FLASH
Light source replaceable	no
Battery Warranty	1 year

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	10 W
Input interface	USB-C

Photometric parameters

Useful luminous flux of the contained light source (Фuse)	600 Lm
Peak luminous intensity	2800 cd
Correlated color temperature	5000K (neutral white)

Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery type	Li-ion 16340
Battery voltage	3.7 V
Battery capacity	800 mAh
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP66
Housing material	Aviation anodized aluminum

Dimensions

EAN	4820246484220
Height	87.4 mm
Depth	22.5 mm
In the package	1 pc.
Outer box	20 pcs.
Width	23 mm
Unit nett weight	59g





INDEX: VLF-A244RH

Signs marking goods

Packaging marking

CE, Utilization











VIDEX VLF-A244RH 600Lm 5000K

INDEX: VLF-A244RH









We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste $\,$



The protection is effective in case of a fall from a height of up to 1 meter



The product is incompatible with light regulators



Operating temperatures range



- The product does not contain mercury



Class of protection against dust and moisture. The product has full protection against dust and powerful water jets

Date: 16.09.2025