

INDEX: VLF-A244RH

TECHNICAL CARD



LED Portable Flashlight



VIDEX VLF-A244RH 600Lm 5000K

INDEX: VLF-A244RH











IP6

Correlated color temperature	5000K (neutral white)
Peak luminous intensity	2800 cd

WARRANTY 3 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutra

General parameters

Operation mode	TURBO, MIDDLE, LOW, MOON, RED HIGH, RED LOW, RED FLASH
Light source replaceable	no

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	10 W
Input interface	USB-C
Input interface	U3D-C

Photometric parameters

Useful lumin	ous flux	of the	contained
light source	(Ф use)		

600 Lm

Additional information

Black
1 m
-20° +40°C
Li-ion 16340
3.7 V
800 mAh
4 level
yes
Does not contain
IP66
Aviation anodized aluminum

Dimensions

EAN	4820246484220
Height	87.4 mm
Depth	22.5 mm
Width	23 mm
In the package	1 pc.
Outer box	20 pcs.
Unit nett weight	59g



VIDEX VLF-A244RH 600Lm 5000K

INDEX: VLF-A244RH

Signs marking goods

Packaging marking

CE, Utilization











VIDEX VLF-A244RH 600Lm 5000K

INDEX: VLF-A244RH









We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste $\,$



The protection is effective in case of a fall from a height of up to 1 meter



The product is incompatible with light regulators



Operating temperatures range



- The product does not contain mercury



Class of protection against dust and moisture. The product has full protection against dust and powerful water jets

Date: 31.05.2025