

## TECHNICAL CARD



LED Portable Flashlight

# VIDEX®



## WARRANTY 3 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrálno bijela / Neutralweiß / Alb neutru / Neutrus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

### General parameters

Operation mode	TURBO, HIGH, MIDDLE, LOW, MOON, STROBE
Light source replaceable	no
Battery Warranty	1 year

### Type of light source

Dimmable	no
Technology	LED

### Electrical parameters

On-mode power (Pon)	10 W
Input interface	USB-C

### Photometric parameters

Useful luminous flux of the contained light source (Φ <sub>use</sub> )	1500 Lm
--	---------

## VIDEX VLF-A298 1500Lm 5000K

### INDEX: VLF-A298

Peak luminous intensity	11960 cd
Correlated color temperature	5000K (neutral white)

### Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery type	Li-ion 18650, Li-ion 16340, Li-ion 18350
Battery voltage	3.7 V
Battery capacity	2200 mAh, 1100 mAh
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP66
Housing material	Anodized aluminum

### Dimensions

EAN	4820246486781
Height	121 mm, 91 mm
Depth	30 mm
In the package	1 pc.
Outer box	20 pcs.
Width	30 mm
Unit nett weight	90g

**VIDEX®**

VIDEX VLF-A298 1500Lm 5000K

INDEX: VLF-A298

**Signs marking goods****Packaging marking**

CE, Utilization



# VIDEX®

VIDEX VLF-A298 1500Lm 5000K

INDEX: VLF-A298



# VIDEX®

VIDEX VLF-A298 1500Lm 5000K

INDEX: VLF-A298



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 1 meter



— The product is incompatible with light regulators



— Operating temperatures range



— The product does not contain mercury



— Class of protection against dust and moisture. The product has full protection against dust and powerful water jets

Date: 21.07.2025