

## TECHNICAL CARD



LED Portable Flashlight

# VIDEX®



## WARRANTY 3 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrálno bijela / Neutralweiß / Alb neutru / Neutrus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

## General parameters

Operation mode	HIGH, LOW, MOON, STROBE
Light source replaceable	no

## Type of light source

Dimmable	no
Technology	LED

## Electrical parameters

On-mode power (Pon)	10 W
Input interface	USB-C

## Photometric parameters

Useful luminous flux of the contained light source (Φ <sub>use</sub> )	600 Lm
Correlated color temperature	5000K (neutral white)

# VIDEX VLF-A352 600Lm 5000K

## INDEX: VLF-A352

Peak luminous intensity 7100 cd

## Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery type	Li-ion 18650
Battery voltage	3.7 V
Battery capacity	2200 mAh
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP66
Housing material	Anodized aluminum

## Dimensions

EAN	4820246485012
Height	124 mm
Depth	27 mm
Width	27 mm
In the package	1 pc.
Outer box	40 pcs.
Unit nett weight	85g

## Signs marking goods

Packaging marking CE, Utilization

# VIDEX®

## VIDEX VLF-A352 600Lm 5000K

### INDEX: VLF-A352



# VIDEX®

VIDEX VLF-A352 600Lm 5000K

INDEX: VLF-A352



**VIDEX<sup>®</sup>****VIDEX VLF-A352 600Lm 5000K****INDEX: VLF-A352**

# VIDEX®

## VIDEX VLF-A352 600Lm 5000K

### INDEX: VLF-A352



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



1m  
SHOCK  
RESISTANT

— The protection is effective in case of a fall from a height of up to 1 meter



Not Dimmable

— The product is incompatible with light regulators



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP66

— Class of protection against dust and moisture.  
The product has full protection against dust and powerful water jets

Date: 31.05.2025