

**INDEX: VLF-A352** 

# **TECHNICAL CARD**



LED Portable Flashlight





#### **INDEX: VLF-A352**













# **WARRANTY 3 YEARS**



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

#### **General parameters**

Operation mode	HIGH, LOW, MOON, STROBE
Light source replaceable	no
Battery Warranty	1 year

### Type of light source

Dimmable	no
Technology	LED

#### **Electrical parameters**

On-mode power (Pon)	10 W
Input interface	USB-C

#### **Photometric parameters**

Useful luminous flux of the contained light source ( <b>Φ</b> use) 600 Lm	the contained 600 Lm
---	----------------------

Correlated color temperature	5000K (neutral white)
Peak luminous intensity	7100 cd

#### **Additional information**

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery type	Li-ion 18650
Battery voltage	3.7 V
Battery capacity	2200 mAh
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP66
Housing material	Anodized aluminum

#### **Dimensions**

EAN	4820246485012
Height	124 mm
Depth	27 mm
In the package	1 pc.
Outer box	40 pcs.
Width	27 mm
Unit nett weight	85g



### **INDEX: VLF-A352**

## Signs marking goods

Packaging marking

CE, Utilization











**INDEX: VLF-A352** 











**INDEX: VLF-A352** 











#### **INDEX: VLF-A352**







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



The protection is effective in case of a fall from a height of up to 1 meter



The product is incompatible with light regulators



- Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture.

— The product has full protection against dust and powerful water jets

Date: 31.07.2025