

**VIDEX<sup>®</sup>**

VIDEX VLF-A505C 5500Lm 5000K

**INDEX: VLF-A505C**

## TECHNICAL CARD



LED Portable Flashlight



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

# VIDEX®



## WARRANTY 3 YEARS

### NEUTRAL WHITE



### 5000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevrtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutrus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

## General parameters

**Light source replaceable** no

## Type of light source

**Dimmable** no

**Technology** LED

## Electrical parameters

**On-mode power (Pon)** 20 W

**Input interface** USB-C

## Photometric parameters

**Useful luminous flux of the contained light source (Φ<sub>use</sub>)** 5500 Lm

**Correlated color temperature** 5000K (neutral white)

**Peak luminous intensity** 20800 cd

## VIDEX VLF-A505C 5500Lm 5000K

### INDEX: VLF-A505C

## Additional information

<b>Housing colour</b>	Black
<b>Fall protection</b>	1 m
<b>Operating temperature range</b>	-20° +40°C
<b>Mercury content</b>	Does not contain
<b>Ingress protection</b>	IP68
<b>Housing material</b>	Aviation anodized aluminum

## Dimensions

<b>EAN</b>	4820246483209
<b>Height</b>	144 mm
<b>Width</b>	49 mm
<b>Depth</b>	26 mm
<b>In the package</b>	1 pc.
<b>Outer box</b>	20 pcs.
<b>Unit nett weight</b>	163g

## Signs marking goods

**Packaging marking** CE, Utilization

**VIDEX®**

VIDEX VLF-A505C 5500Lm 5000K

**INDEX: VLF-A505C**

**VIDEX<sup>®</sup>**

VIDEX VLF-A505C 5500Lm 5000K

**INDEX: VLF-A505C**

# VIDEX®

VIDEX VLF-A505C 5500Lm 5000K

INDEX: VLF-A505C



**VIDEX®**  
MODEL | A505C

EXTRA HIGH POWER RECHARGEABLE FLASHLIGHT

**5500**  
MAX LUMENS

- LONG-RANGE BEAM 500M
- FLUX STABILIZATION
- IP68
- 1m SHOCKPROOF

**VIDEX®**  
MODEL | A505C

4X LUMINUS SST40  
20W  
5000K (Neutral white)

Excellent performance with four powerful LED chips. Maximum luminous flux 5500 Lumen, long-range beam distance up to 500 meters and high intensity 20800cd.

# VIDEX®

## VIDEX VLF-A505C 5500Lm 5000K

### INDEX: VLF-A505C



# VIDEX®

VIDEX VLF-A505C 5500Lm 5000K

INDEX: VLF-A505C

**VIDEX®**  
MODEL | A505C

INTEGRATED FOUR-LEVEL LED BATTERY INDICATOR



CHARGE 100-85%    CHARGE 85-50%    CHARGE 50-25%    CHARGE 25-1%

**VIDEX®**  
MODEL | A505C

PROTECTION GRADE IP68



The flashlight can work stably when immersed for 30 minutes at a depth of up to 2 meters.

**VIDEX®**  
MODEL | A505C

FAST CHARGE PORT TYPE-C




Charge the battery 4000mAh directly inside the flashlight for around 2.5 hours. Silicone cover protects the charging port from dust and water.

**VIDEX®**  
MODEL | A505C

TEMPERED GLASS



Tempered glass withstands high temperatures, is resistant to scratches, and is not subject to yellowing.

# VIDEX®

## VIDEX VLF-A505C 5500Lm 5000K

### INDEX: VLF-A505C



**VIDEX®**  
MODEL | A505C

PROGRAM ROOT

Start position	Action A	Result	Action B	Result
OFF	Press and hold for 0.5 sec	ON	Press and hold for 0.5 sec	OFF
ON	Click	> MOON > LOW > MIDDLE > HIGH > TURBO >		
ON/OFF	Press and hold for 3 sec	STROBE	Click	Exit
OFF	Click	Battery status		
OFF	Double click	Lock	Double click	Unlock

Notes: The flashlight automatically memorizes the last selected lighting mode (excluding Strobe mode) and applies it next time when turned on. Battery indication is always on if the light is switched on.

**VIDEX®**  
MODEL | A505C

KIT CONTENT

- SPARE SILICONE RINGS
- 18650 ADAPTER
- USER'S MANUAL, WARRANTY CARD
- LI-ION BATTERY
- FLASHLIGHT
- CHARGING CABLE
- LANYARD

SIZE 144x49mm  
WEIGHT 163g (without battery)

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.

Date: 23.02.2025