

VIDEX-PANEL-LED-36W-PB364W-NW

INDEX: VLE-PB364W

TECHNICAL CARD



LED Recessed-mounted Panel













VIDEX-PANEL-LED-36W-PB364W-NW

INDEX: VLE-PB364W



Ra ≥ 80









50 000 h

Free

Not Dimmable









Technology LED Energy efficiency class of the contained light source

WARRANTY 3 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Light source or containing product	Containing product
Control gear replaceable	by the producer
Light source replaceable	by the producer

Type of light source

Dimmable	no
Directional (DLS) or non-directional (NDLS) light source	NDLS
Connected light source (cls)	no
Color-tunable light source	no
Mains (MLS) or non-mains (NMLS) light source	NMLS
High luminance light source	No
Anti-glare shield	No

Electrical parameters

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	230 mA
Input interface	Terminal block
Electric shock protection class	II
Displacement factor (cos φ1)	-
Survival factor	0.9
Energy consumption in on-mode of the light source (kWh/1000h)	36

Photometric parameters

Useful luminous flux of the contained light source (Фuse)	6400 Lm
Correlated color temperature	4000K (neutral white)
Beam angle	160°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	50000 h
Useful luminous flux of the light source reference	in a sphere (360°)
Chromaticity coordinates (x)	0.38
Chromaticity coordinates (y)	0.38
R9 colour rendering index value	>0
The lumen maintenance factor	≥96%



VIDEX-PANEL-LED-36W-PB364W-NW

INDEX: VLE-PB364W

Flicker metric (Pst LM)	-
Stroboscopic effect metric (SVM)	-
Colour consistency in MacAdam ellipses (SDCM)	<6 (4000K)
CRI Min	Ra 80
CRI Max	Ra 89

Width	595 mm
Depth	28 mm
Unit nett weight	1.31kg x2

Signs marking goods

	Recycling of
Packaging marking	waste, CE,
	Utilization


Additional information

Place of installation	Armstrong ceiling, Ceiling
Place of application	indoor
Housing colour	White
Diffuser material	Polystyrene (PS)
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Suitable for installation in normally flammable surfaces	yes
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum, Iron alloy, Acrylic




Dimensions

EAN	5904405542651
In the package	2 pc.
Outer box	8 pcs.
Height	595 mm







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

VIDEX-PANEL-LED-36W-PB364W-NW

INDEX: VLE-PB364W



The product must be used indoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced



The product can be installed and used in/on normally flammable surfaces



Waste recycling after the end of the product's service life



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Ra > 80 - color rendering index



Rated On/off cycles



Nominal lifetime (hours)



The product does not emit ultraviolet light



The product is incompatible with light regulators



Operating temperatures range



Colour consistency in MacAdam ellipses (SDCM)



The product does not contain mercury



Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection

against moisture

Date: 18.11.2025