

INDEX: VLE-TF18B

TECHNICAL CARD



LED Rechargeable Desk Lamp











DC 5 V



VIDEX VLE-TF18B Black

INDEX: VLE-TF18B

Rated voltage, frequency






















20 000



CCT 3000K CCT 4000K CCT 5500K







Survival factor

WARRANTY 2 YEARS

General parameters

Control gear replaceable	no
Light source replaceable	no
Light source or containing product	Containing product

Type of light source

Electrical parameters

Dimmable	3-step
Directional or non-directional light source	-
Mains or non-mains light source	-
Connected light source (cls)	-
Colour-tuneable light source (CTLS)	yes
High luminance light source	-
Anti-glare shield	-
Technology	LED

On-mode power (Pon)	3 W

Photometric parameters

Correlated color temperature	5500K (cold white), 4000K (neutral white), 3000K (warm white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
Lifetime	30000 h
On/Off cycles	20000
Chromaticity coordinates (x)	0.38
Chromaticity coordinates (y)	0.38
R9 colour rendering index value	-
The lumen maintenance factor	-
Colour consistency in MacAdam ellipses (SDCM)	<6 (3000K), <6 (4000K), <6 (5500K)
Flicker metric (Pst LM)	-
Stroboscopic effect metric (SVM)	-

Additional information

Place of installation	Desk
Place of application	indoor



INDEX: VLE-TF18B

Housing colour	Black
Ultraviolet radiation	no
Operating temperature range	-10° +40°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	PC, PP, PS

Dimensions

EAN	5904405542552
Height	356 mm
Width	120 mm
Depth	120 mm
Outer box	20 pcs.
In the package	1 pc.

Signs marking goods

	Recycling of
Packaging marking	waste, CE,
	Utilization







INDEX: VLE-TF18B












INDEX: VLE-TF18B









We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

Date: 22.12.2024