

TECHNICAL CARD



LED RECHARGEABLE LIGHT with MOTION SENSOR



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.



120°



Ra ≥ 80



Free



-20° +40°C



Dimmable



Free



IP20

WARRANTY 2 YEARS

General parameters

Light source replaceable	no
--------------------------	----

Type of light source

Dimmable	yes
----------	-----

Technology	LED
------------	-----

Electrical parameters

On-mode power (Pon)	1.5 W
---------------------	-------

Input interface	USB-C
-----------------	-------

Electric shock protection class	III
---------------------------------	-----

Photometric parameters

Useful luminous flux of the light source (Φ _{use})	150 Lm
--	--------

Correlated color temperature	6500K (cold white), 4000K (neutral white), 3000K (warm white)
------------------------------	---

Beam angle	120°
------------	------

Color rendering index (CRI)	Ra > 80
-----------------------------	---------

VIDEX VL-NL013W-SR

INDEX: VL-NL013W-SR

CRI Min	Ra 80
---------	-------

CRI Max	Ra 88
---------	-------

Additional information

Place of application	indoor
----------------------	--------

Housing colour	White
----------------	-------

Ultraviolet radiation	no
-----------------------	----

Motion sensor	yes
---------------	-----

Sensor type	PIR
-------------	-----

Sensor detection angle	120°
------------------------	------

Sensor time delay	20 s
-------------------	------

Sensor detection distance	≤6 m
---------------------------	------

Operating temperature range	-20° +40°C
-----------------------------	------------

Mercury content	Does not contain
-----------------	------------------

Ingress protection	IP20
--------------------	------

Housing material	ABS
------------------	-----

Dimensions

EAN	4820246486453
-----	---------------

Height	300 mm
--------	--------

Width	40 mm
-------	-------

Depth	29 mm
-------	-------

In the package	1 pc.
----------------	-------

Outer box	24 pcs.
-----------	---------

Unit nett weight	155g
------------------	------

Signs marking goods

VIDEX®

VIDEX VL-NL013W-SR

INDEX: VL-NL013W-SR

Packaging marking

Recycling of
waste, CE,
Utilization



VIDEX[®]

VIDEX VL-NL013W-SR

INDEX: VL-NL013W-SR

MAGNETIC
FASTENING

VIDEX®

VIDEX VL-NL013W-SR

INDEX: VL-NL013W-SR




HANGING
LOOP



INDEX: VL-NL013W-SR

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.

