

**INDEX: VL-NL049W-R** 

# **TECHNICAL CARD**





LED RECHARGEABLE LIGHT with REMOTE CONTROL













### **INDEX: VL-NL049W-R**











20112	<b>*/</b> /		(
Ra ≥ 80	Free	Dimmable	-20°

CRI Min	Ra 80
CRI Max	Ra 88



## **WARRANTY 2 YEARS**

## **General parameters**

Light source replaceable no
-----------------------------

## Type of light source

Dimmable	yes
Technology	LED

## **Electrical parameters**

On-mode power (Pon)	1.5 W
Input interface	USB-C
Electric shock protection class	III

## **Photometric parameters**

Luminous flux	150 Lm
Correlated color temperature	6500K (cold white), 4500K (neutral white), 3000K (warm white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80

#### **Additional information**

Place of application	indoor
Housing colour	White
Ultraviolet radiation	no
Motion sensor	no
Operating temperature range	-20° +40°C
Battery voltage	3.7 V
Battery type	Li-pol
Battery capacity	2200 mAh
Battery replaceable	no
Mercury content	Does not contain
Ingress protection	IP20
Housing material	ABS

#### **Dimensions**

EAN	4820246485326
In the package	1 pc.
Height	300 mm
Outer box	24 pcs.
Width	39 mm
Depth	36 mm
Unit nett weight	150g

## Signs marking goods



## **INDEX: VL-NL049W-R**

## **Packaging marking**

Recycling of waste, CE, Utilization











## INDEX: VL-NL049W-R











## INDEX: VL-NL049W-R








#### **INDEX: VL-NL049W-R**







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product must be used indoors



Class III protection against electric shock - ensured by supplying a specific product with a safe very low voltage (SELV) without the risk of creating a voltage above safe levels



Waste recycling after the end of the product's service life



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— Rated beam angle



— Ra > 80 - color rendering index



— The product does not emit ultraviolet light



The product supports brightness adjustment



Operating temperatures range



- The product does not contain mercury



Class of protection against dust and moisture.

Protection against solid objects larger than 12 mm; no protection against moisture

Date: 18.11.2025