


TECHNICAL CARD



LED Solar Floodlight



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.



WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrálno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

General parameters

Light source replaceable no

Type of light source

Dimmable yes

Technology LED

Electrical parameters

Cable length 1 m

Electric shock protection class III

Displacement factor (cos φ1) -

Photometric parameters

Luminous flux 1000 Lm

VIDEX VL-FS02-505

INDEX: VL-FS02-505

Correlated color temperature	5000K (neutral white)
Beam angle	90°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	30000 h
Chromaticity coordinates (x)	0.34
Chromaticity coordinates (y)	0.359

Additional information


Battery power	32 Wh
Vertical adjustment range	180°
Place of installation	Flat surface, Wall
Place of application	outdoor
Impact protection	IK07
Housing colour	Gray
Diffuser material	Polycarbonate (PC)
Minimum distance from the illuminated object	0.5 m
Motion sensor	no
Operating temperature range	-20° +50°C
Battery type	LiFePO4
Battery voltage	3.2 V
Battery capacity	10000 mAh
Battery replaceable	no
Mercury content	Does not contain
Ingress protection	IP65


Housing material Aluminum alloy

Dimensions

EAN	4820118298924
Height	207 mm
Depth	22.5 mm
Outer box	10 pcs.
Width	160 mm



VIDEX[®]**VIDEX VL-FS02-505****INDEX: VL-FS02-505**

INDEX: VL-FS02-505


We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



The product must be used outdoors



Class III protection against electric shock - ensured by supplying a specific product with a safe very low voltage (SELV) without the risk of creating a voltage above safe levels



Minimum distance from the illuminated object



Rated beam angle



Ra > 80 - color rendering index



Rated On/off cycles



The product withstands a medium impact (e.g., from a blunt object)



Nominal lifetime (hours)



The product supports brightness adjustment



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture.
The product has full protection against dust and water jets from all directions