

VIDEX 30W 5000K

INDEX: VL-FSO-1005

# **TECHNICAL CARD**



LED Solar Floodlight











#### **VIDEX 30W 5000K**

#### **INDEX: VL-FSO-1005**























# Dimmable -20°C +50°C Free



**WARRANTY 2 YEARS** 

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutra

#### **General parameters**

Light source replaceable	no
Eight Source replaceable	110

#### Type of light source

Dimmable	yes
Technology	LED

#### **Electrical parameters**

1 m	Cable length
III	Electric shock protection class
-	Displacement factor (cos φ1)
- -	

#### **Photometric parameters**

Luminous flux 2800 Lm	

Correlated color temperature	5000K (neutral white)
Beam angle	90°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	30000 h

#### **Additional information**

Battery power	96 Wh
Vertical adjustment range	180°
Place of installation	Flat surface, Wall
Place of application	outdoor
Impact protection	IK07
Housing colour	Gray
Diffuser material	Polycarbonate (PC)
Minimum distance from the illuminated object	0.5 m
Motion sensor	no
Operating temperature range	-20° +50°C
Battery voltage	3.2 V
Battery type	LiFePO4
Battery capacity	30000 mAh
Battery replaceable	no
Mercury content	Does not contain
Ingress protection	IP65
Housing material	Aluminum alloy



### VIDEX 30W 5000K

### INDEX: VL-FSO-1005

## **Dimensions**

EAN	4820118298948
In the package	1 pc.
Outer box	3 pcs.
Height	282 mm
Width	250 mm
Depth	42 mm
Unit nett weight	4.3kg



## Signs marking goods

Packaging marking

CE, Utilization







Σ

251 мм

#### **VIDEX 30W 5000K**

#### **INDEX: VL-FSO-1005**

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product must be used outdoors



Class III protection against electric shock - ensured by supplying a specific product with a safe very low voltage (SELV) without the risk of creating a voltage above safe levels



Minimum distance from the illuminated object



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Rated beam angle



Ra > 80 - color rendering index



Rated On/off cycles



The product withstands a medium impact (e.g., from a blunt object)



Nominal lifetime (hours)



The product supports brightness adjustment




Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions



180°

Date: 26.11.2025