

TECHNICAL CARD



LED Street Light



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



90×130°



Ra ≥ 80



30 000 h

ON/OFF
20 000

IK07



Not Dimmable



CCT 6500K



Free



IP65

WARRANTY 3 YEARS

NEUTRAL WHITE



5000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

General parameters

Control gear replaceable	-
Light source replaceable	no
Light source or containing product	Light source

Type of light source

Energy class of the light source	E
Dimmable	no
Directional or non-directional light source	DLS
Mains or non-mains light source	MLS
Connected light source (cls)	no
Colour-tuneable light source (CTLS)	no
Technology	LED

Electrical parameters

VIDEX-STREET-LED-LEYA-50W-NW5

INDEX: VLE-SLE14-505

On-mode power (Pon)	50 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Cable length	30 cm
Rated current	240 mA
Input interface	Free wire ends
Electric shock protection class	I
Energy consumption in on-mode of the light source (kWh/1000h)	50
Displacement factor (cos φ1)	0.9
Survival factor	0.9

Photometric parameters

Useful luminous flux of the light source (Φuse)	5000 Lm
Correlated color temperature	5000K (neutral white)
Peak luminous intensity	3100 cd
Beam angle	90 × 130°
Color rendering index (CRI)	Ra > 80
Lifetime	30000 h
On/Off cycles	20000
Useful luminous flux of the light source reference	in a wide cone (120°)
Chromaticity coordinates (x)	0.34
Chromaticity coordinates (y)	0.359
R9 colour rendering index value	>0
The lumen maintenance factor	≥96%
Colour consistency in MacAdam ellipses (SDCM)	<6 (6500K)

INDEX: VLE-SLE14-505

Flicker metric (Pst LM)	≤1
Stroboscopic effect metric (SVM)	outdoor use

Additional information

Place of installation	Pillar, Wall
Vertical adjustment range	200°
Place of application	outdoor
Housing colour	Gray
Impact protection	IK07
Minimum distance from the illuminated object	0.5 m
Diffuser material	PC
Operating temperature range	-20° +50°C
Suitable for installation in normally flammable surfaces	yes
Mercury content	Does not contain
Ingress protection	IP65
Housing material	Aluminum alloy

Dimensions


EAN	5904405542293
Height	487 mm
Width	151 mm
Depth	88 mm
Outer box	10 pcs.
In the package	1 pc.



VIDEX®

VIDEX-STREET-LED-LEYA-50W-NW5

INDEX: VLE-SLE14-505



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegra Opt Sp. z o.o., Handlowa 23, 05-120 Legionowo, Poland.

Date: 29.09.2024